

МРЕЖОВА ТЕХНИКА > СУИЧОВЕ

Cisco Meraki MS350-24X L3 Stck Cld-Mngd 24xGigE mGig UPOE Switch



Модел : MS350-24X-HW

Cisco Meraki MS350-24X L3 Stck Cld-Mngd 24xGigE mGig UPOE Switch

Суич, тип: Fixed Port

Общ брой портове: 28

Основни портове, тип: 16x10/100/1000Base-T +

8x100M/1G/2.5G/5G/10G

Power Over Ethernet (PoE): Available PoE+ Power: 740 W

Uplink портове: 4x10GE SFP

Свободни (10GB) слотове: No

Управление: Managed via the Web with the Meraki cloud management platform; Integrated with Meraki Wireless and complete portfolio of IT products and solutions; SNMP and SYSLOG support for integration with other network management solutions

Stackable: 2 x stacking ports; Physically stack up to 8 switches with 160 Gbps of stacking bandwidth; Virtual Stacking supports thousands of switch ports in a single logical stack for unified management, monitoring, and configuration

Fans: Variable speed fans

Захранване: Hot-swappable Power Supply Configuration; Supported Power Supply: 2 x 1025W PSU (Single power supply (PSU) included. For redundancy, second PSU is sold separately)

Routing: Layer 3 Advanced

Памет (Flash, RAM): -

Капацитет за маршрутизиране/превключване, Gbps: 272 Gbps

Пропускателна способност, Mpps: 202.38 Mpps

MAC адреси: 512000 MAC address table size

VLAN (брой, стандарти): 802.1Q VLAN and trunking support for up to 4094 VLANs

QoS: 802.1p Quality of Service, 8 queues (w/ 6 configurable for DSCP-to-CoS mapping)

L2 мрежови стандарти: IEEE 802.3, IEEE 802.3u, IEEE 802.3af, IEEE 802.3at, IEEE 802.1D, IEEE 802.1Q, IEEE 802.1p, IEEE 802.3ad, IEEE 802.1w, IEEE 802.1x, IEEE 802.1ab

L3 мрежови стандарти: Static routing, OSPFv2 (with support for up to 16 ECMP Routes), Multicast routing, Warm Spare (VRRP) - OSPF and Warm Spare do not operate concurrently, DHCP Server, DHCP Relay

IPv6 functionality: -

Сигурност: Integrated multi-factor authentication for Dashboard management; Role-based access control (RBAC) with granular device and configuration control; IEEE 802.1X RADIUS and MAB, hybrid authentication and RADIUS server testing; IPv4 and IPv6 ACLs

Размери (Ш, Д, В), mm: 485 x 595 x 44

Опция за монтаж: Rackmount

Цена : 5035.51 EUR с ДДС

Наличност: Този продукт е бил добавен в нашия каталог на Вт 27 януари, 2026