

МРЕЖОВА ТЕХНИКА &gt; РУТЕРИ

## ASUS DSL-N55U ADSL WL N ROUTER



Модел : ASUS DSL-N55U ADSL WL N ROUTER

ASUS DSL-N55U ADSL WL N ROUTER

Manufacturer: ASUS

Mnfr Part #: -

Model: DSL-N55U ADSL

Interface: 1 x RJ11 for ADSL; 4 x RJ45 for 10/100/Gigabits BaseT for LAN; USB 2.0 x 2; Detachable dBi dipole antenna x 3; WPS Button, Reset Button, Power Switch, Wireless on/off Switch.

Standarts: IEEE 802.11a, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n, IEEE 802.11d; IEEE 802.3, IEEE 802.3u, IEEE 802.11i, IEEE 802.11e, IPv4, IPv6.

Data Rate: Wi-Fi Data Rate: 802.11a :

6,9,12,18,24,36,48,54Mbps; 802.11b : 1, 2, 5.5, 11Mbps;

802.11g : 6,9,12,18,24,36,48,54Mbps; 802.11n : up to

600Mbps; xDSL Data Rate: ANSI T1.413 Issue 2; ITU-T

G.992.1 Annex A (G.dmt): ITU-T G.992.2 (G.lite): ITU-T

G.994.1 (G.hs): ITU-T G.992.3 (G.dmt.bis): ITU-T G.992.5

Annex A/M; ADSL 2/2+ 24Mbps downstream.

Frequency: 2.4GHz /5GHz

VPN Support: IPSec Pass-Through; PPTP Pass-Through; L2TP Pass-Through; PPTP server.

Security: 64-bit WEP, 128-bit WEP, WPA2-PSK, WPA-PSK, WPA-Enterprise, WPA2-Enterprise, Radius with 802.1x, WPS support Firewall & Access Control Built-in NAT and SPI firewall Port, IP packet, URL, MAC filter

Management: Web-based GUI configuration; Firmware upgraded, configuration data uploaded and downloaded via Web-based GUI; UPnP IGD 1.0; Auto VPI/VCI detection; Configuration backup and restore; Diagnostics; Log & Trace function.

Protocol: -

Environment: Operating Temperature: -10 &amp;deg;C to 50

&amp;deg;C (14 &amp;deg;F to 122 ?F); Storage Temperature: -40

&amp;deg; to 60 &amp;deg; C (-40 &amp;deg;F to 140 &amp;deg;F); Operating

Humidity: 5 % to 95 % (Non-condensing); Storage Humidity:

5 % to 95 % (Non-condensing).

Certifications: CE, C-Tick, Telepermit, IDA, PCT, Wi-Fi

LED Indicator: Power, ADSL, Internet, WLAN, LAN x 4

Dimensions: 207 x 148.8 x 35.5 mm

Warranty: 36 Months

Цена : 56.94&amp;nbsp;EUR с ДДС



*Наличност: Този продукт е бил добавен в нашия каталог на Пт 25 септември, 2026*

*March 17, 2026, 7:24 am*