

КОМПЮТЪРНИ КОМПОНЕНТИ > Дънни Платки

ASUS PRIME A520M-K / AM4



Модел : ASUS PRIME A520M-K / AM4

ASUS PRIME A520M-K / AM4

Graphics: 1 x D-Sub; 1 x HDMI 2.1(4K@60HZ)

CPU's supported: Build in AMD AM4 Socket Processors *

Chipset: AMD A520

Expansion Slots: 3rd Gen AMD Ryzen™; and 3rd Gen AMD Ryzen™; with Radeon™; Graphics Processors; 1 x PCIe 3.0 x16 (x16 mode); AMD A520 Chipset; 2 x PCIe 3.0 x1

Storage: Total supports 1 x M.2 slot(s) and 4 x SATA 6Gb/s ports; 3rd Gen AMD Ryzen™; and 3rd Gen AMD Ryzen™; with Radeon™; Graphics Processors : 1 x M.2 Socket 3, with M Key, Type 2242/2260/2280 (PCIe 3.0 x4 and SATA modes) storage devices support; AMD A520 Chipset : 4 x SATA 6Gb/s port(s);, Support Raid 0, 1, 10
Memory type: 2 x DIMM, Max. 64GB, DDR4 4600(O.C.)/4400(O.C.)/4000(O.C.)/3866(O.C.)/3733(O.C.)/3600(O.C.)/3466(O.C.)/3333(O.C.)/3200/3000/2800/2666/2400/2133 MHz Un-buffered Memory *; Dual Channel Memory Architecture; ECC Memory (ECC mode) support varies by CPU.

I/O: 1 x PS/2 keyboard/mouse combo port(s); 1 x D-Sub; 1 x HDMI; 1 x LAN (RJ45) port(s); 4 x USB 3.2 Gen 1 (blue) Type-A; 2 x USB 2.0; 3 x Audio jack(s)

Connectors: 1 x CPU Fan connector(s); 1 x Chassis Fan connector(s); 1 x USB 3.2 Gen 1(up to 5Gbps) connector(s) support(s) additional 2 USB 3.2 Gen 1 port(s); 2 x USB 2.0 connector(s) support(s) additional 4 USB 2.0 port(s); 1 x M.2 Socket 3 with M key, type 2242/2260/2280 storage devices support (SATA & PCIe 3.0 x 4 mode); 1 x SPI TPM header; 4 x SATA 6Gb/s connector(s); 1 x S/PDIF out header(s); 1 x 24-pin EATX Power connector(s); 1 x 8-pin EATX 12V Power connectors; 1 x Front panel audio connector(s) (AAFP); 1 x Clear CMOS jumper(s); 1 x System panel connector; 1 x COM port header; 1 x Speaker connector

Audio: Realtek ALC887 7.1 Surround Sound High Definition Audio CODEC *; - Supports : Jack-detection, Multi-streaming, Front Panel Jack-retasking, up to 24-Bit/192kHz playback; Audio Feature : - Audio Shielding; - Dedicated audio PCB layers; * Choose the chassis with HD audio module in fr
LAN: Realtek RTL8111H 1Gb Ethernet; ASUS LANGuard
BIOS: 256 Mb Flash ROM, UEFI AMI BIOS



Form Factor: mATX Form Factor; 8.9 inch x 8.7 inch (22.6 cm x 22.1 cm)

OS: Windows®; 10 64-bit

Warranty: 36 Months

Цена : 64.14 EUR с ДДС

Наличност: Този продукт е бил добавен в нашия каталог на Пт 02 октомври, 2026

April 8, 2026, 8:38 AM