

КОМПЮТЪРНИ КОМПОНЕНТИ > Дънни Платки

ASUS PRIME B450M-K II /AM4



Модел : ASUS PRIME B450M-K II /AM4

ASUS PRIME B450M-K II /AM4

Graphics: Integrated Graphics in the 2nd and 1st Gen AMD Ryzen™; with Radeon™; Vega Graphics/ Athlon™; with Radeon™; Vega Graphics Processors *; 1 x D-Sub; 1 x DVI-D; 1 x HDMI 2.0b

CPU's supported: AMD AM4 Socket for 3rd/2nd/1st Gen AMD Ryzen™;/2nd and 1st Gen AMD Ryzen™; with Radeon™; Vega Graphics/Athlon™; with Radeon™; Vega Graphics Processors *

Chipset: AMD B450

Expansion Slots: 3rd/2nd/1st Gen AMD Ryzen™; Processors; 1 x PCIe 3.0 x16 (x16 mode); 2nd and 1st Gen AMD Ryzen™; with Radeon™; Vega Graphics Processors; 1 x PCIe 3.0 x16 (x8 mode); AMD Athlon™; with Radeon™; Vega Graphics Processors; 1 x PCIe 3.0 x16 (x4 mode); AMD B450 chipset; 2 x PCIe 2.0 x1 Storage: Total supports 1 x M.2 slot(s) and 4 x SATA 6Gb/s ports; 3rd/2nd/1st Gen AMD Ryzen™;/ 2nd and 1st Gen AMD Ryzen™; with Radeon™; Vega Graphics : 1 x M.2 Socket 3, with M key, type 2242/2260/2280 storage devices support (SATA & PCIE 3.0 x 4 mode); Athlon™; with Radeon™; Vega Graphics Processors : 1 x M.2 Socket 3, with M key, type 2242/2260/2280 storage devices support (SATA mode); AMD B450 chipset : 4 x SATA 6Gb/s port(s);, Support Raid 0, 1, 10 Memory type: 3rd/2nd/1st Gen AMD Ryzen™;/ 2nd and 1st Gen AMD Ryzen™; with Radeon™; Vega Graphics/ Athlon™; with Radeon™; Vega Graphics Processors; 2 x DIMM, Max. 64GB, DDR4

4400(O.C.)/4000(O.C.)/3866(O.C.)/3733(O.C.)/3600(O.C.)/3466(O.C.)/3400(O.C.)/3300(O.C.)/3200(O.C.)/3000(O.C.)/2933(O.C.)/2800(O.C.)/2666/2400/2133 MHz Un-buffered Memory *; Dual Channel Memory Architecture; ECC Memory (ECC mode) support varies by CPU.

I/O: 1 x PS/2 keyboard/mouse combo port(s); 1 x DVI-D; 1 x D-Sub; 1 x HDMI; 1 x LAN (RJ45) port(s); 4 x USB 3.2 Gen 1 (blue) Type-A; 2 x USB 2.0; 3 x Audio jack(s); 1 x BIOS FlashBack™; Button(s)

Connectors: 1 x CPU Fan connector(s) (1 x 4 -pin); 1 x Chassis Fan connector(s) (1 x 4 -pin); 1 x USB 3.2 Gen 1(up to 5Gbps) connector(s) support(s) additional 2 USB 3.2 Gen 1 port(s) (19-pin); 2 x USB 2.0 connector(s) support(s)

additional 4 USB 2.0 port(s); 1 x M.2 Socket 3 with M key, type 2242/2260/2280 storage devices support (SATA & PCIE 3.0 x 4 mode); 1 x SPI TPM header; 1 x COM port(s) connector(s); 4 x SATA 6Gb/s connector(s); 1 x S/PDIF out header(s); 1 x 24-pin EATX Power connector(s); 1 x 8-pin ATX 12V Power connector(s); 1 x Front panel audio connector(s) (AAFP); 1 x System panel(s); 1 x Clear CMOS jumper(s); 1 x COM port header; 1 x Speaker connector

Audio: Realtek ALC887/897 7.1-Channel High Definition Audio CODEC *; - Supports : Jack-detection, Multi-streaming, Front Panel Jack-retasking, up to 24-Bit/192kHz playback; Audio Feature : - LED-illuminated design; - Audio Shielding; - Dedicated audio PCB layers; - Premium Japanese audio capacitors; * Choose the chassis with HD audio module in front panel to support 8-channel audio output.

LAN: Realtek® RTL8111H; ASUS LANGuard

BIOS: 256 Mb Flash ROM, UEFI AMI BIOS

Form Factor: mATX Form Factor; 8.9 inch x 8.7 inch (22.6 cm x 22.1 cm)

OS: Windows®; 10 64-bit; Windows®; 7 64-bit *

Warranty: 36 Months

Цена : 63.38 EUR с ДДС

Наличност: Този продукт е бил добавен в нашия каталог на Ср 25 ноември, 2026