МРЕЖОВА ТЕХНИКА > СУИЧОВЕ

D-Link 24-port Gigabit Smart Managed Switch with 4x 10G SFP+ ports



Модел : DGS-1250-28X
D-Link 24-port Gigabit Smart Managed Switch with 4x 10G SFP+ ports
Суич, тип: Fixed Port
Общ брой портове: 28
Основни портове, тип: 24x 10/100/1000Mbps Auto-Negotiating Ports
Power Over Ethernet (PoE): -
Uplink портове: 4x 10G SFP+ ports
Свободни (10GB) слотове: -
Управление: Web-based GUI, D-Link Network Assistant, Compact CLI, Telnet Server, TFTP Client, Configurable MDI/MDIX, SNMP, BootP/DHCP Client, System Log, SNTP, ICMP v6, IPv4/v6 Dual Stack, DHCP Auto Configuration, RMONv1
Stackable: IPv4/v6 Dual Stack
Fans: -
Захранване: internal universal power supply (100 to 240 V AC 50/60 Hz), Power Consumption: 29.6W Max., 9.3 W Standby
Routing: Static (124 IPv4 static route entries, 50 IPv6 static route entries)
Памет (Flash, RAM): 64 MB Flash, 12 Mbits Packet Buffer Memory; CPU memory: 2G DDR3
Капацитет за маршрутизиране/превключване, Gbps: 128 Gbps
Пропускателна способност, Mpps: 95.24 Mpps
MAC адреси: 16000 MAC address table size
VLAN (брой, стандарти): 802.1Q, VLAN Group, Max. 4094 static VLAN groups, Configurable VID from 1 - 4094, Asymmetric / Auto Voice VLAN, Max. 10 user-defined OUI, Max. 8 default OUI, Auto Surveillance VLAN
QoS: 802.1p, 8 queues per port, Queue Handling (Strict, WRR), Bandwidth Control - Port-based (ingress/egress, min granularity 10/100/1000 is 16 Kbps), DSCP, MAC address, EtherType, IP address, ToS, IP preference, IPv6 Traffic Class, TCP/UDP port
L2 мрежови стандарти: IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3z, IEEE 802.3az, IEEE 802.3x, IEEE 802.3ae
IPv6 functionality: IPv6 Neighbor Discovery (ND); IPv6 address: Source/destination IP address mask, DSCP mask, Protocol type mask, TCP/UDP port number mask, IPv6 traffic

November 23, 2020, 6:0

class mask
Сигурност: Broadcast/Multicast/Unicast Storm Control, D-Link Safeguard Engine, Traffic segmentation, SSH v2, TLS v.1.2, DoS attack prevention, 802.1X, Port Security, ARP Spoofing Prevention, DHCP, IP-MAC-Port Binding, ARP, DHCP, IPv4/6 inspection
Размери (Ш, Д, В), mm: 440 x 140 x 44
Опция за монтаж: Rackmount
Други: RJ-45 console Port for CLI management

Цена : 146.96 EUR с ДДС

Наличност: Този продукт е бил добавен в нашия каталог на Чт 17 декември, 2026

November 23, 2026, 6:00 a