МРЕЖОВА ТЕХНИКА > СУИЧОВЕ

Dell EMC Powerswitch N2224X-ON, 24x1/2.5G, 4x25G, 2x40G Stacking, 1xAC PSU, IO/PS airflow, OS6, Lifetime Limited Hardware Warranty



Модел : DNN2224X
Dell EMC Powerswitch N2224X-ON, 24x1/2.5G, 4x25G, 2x40G Stacking, 1xAC PSU, IO/PS airflow, OS6, Lifetime Limited Hardware Warranty
Суич, тип: Fixed Port
Общ брой портове: 30
Основни портове, тип: 24x RJ-45 10/100/1000/2500BASE-T ports
Power Over Ethernet (PoE): -
Uplink портове: 4x SFP28 ports
Свободни (10GB) слотове: -
Управление: CLI, Web, SNMP
Stackable: 2x QSFP+ (40G per port)
Fans: x 2
Захранване: 550W AC hot swappable with IO/PS airflow
Routing: Layer 3 routing (Static routes: 1256 (IPv4)/128 (IPv6) Dynamic routes: 256 (IPv4), RIP routing interfaces: 256, VLAN routing interfaces: 128)
Памет (Flash, RAM): CPU memory: 4GB, SSD: 8GB, Packet buffer memory: 4MB
Капацитет за маршрутизиране/превключване, Gbps: 480 Gbps
Пропускателна способност, Mpps: 667 Mpps
MAC адреси: 32K
VLAN (брой, стандарти): Private VLAN extensions and Private VLAN Edge support. VLAN routing interfaces: 128, VLANs supported: 4094, Protocol-based VLANs: Supported
QoS: Port Based QoS (TCP/UDP) Services Mode, Flow Based QoS Services Mode (IPv4/IPv6), srTCM, trTCM, L4 Trusted Mode, UDLD, Assured Fwd PHB, DiffServ Field, DiffServ Architecture
L2 мрежови стандарти: 802.3ab, 802.3ac, 802.3ad, 802.3ae, 802.3at, 802.3ax, 802.3u, 802.3x, 802.3z
L3 мрежови стандарти: RIP, OSPF
IPv6 functionality: Static routing, RIP, and OSPF support
Сигурност: RADIUS, TACACS+, 802.1x
Размери (Ш, Д, В), mm: 434 x 400 x 43.5
Опция за монтаж: Rackmount, 1 RU
Други: OS6, RJ-45 and Type-B micro USB 3.0 console ports

Цена : 5508.00 EUR с ДДС

Наличност: Този продукт е бил добавен в нашия каталог на Пн 18 май, 2026

November 23, 2026, 5:58 a