МРЕЖОВА ТЕХНИКА > СУИЧОВЕ

Dell EMC PowerSwitch N3248P-ON, 48x1G, 4x10G SFP+, 2x100G QSFP28, PoE 30W, 1xAC PSU, IO/PS, OS6, Lifetime Limited Hardware Warranty



Модел : DNN3248P
Dell EMC PowerSwitch N3248P-ON, 48x1G, 4x10G SFP+, 2x100G QSFP28, PoE 30W, 1xAC PSU, IO/PS, OS6, Lifetime Limited Hardware Warranty
Суич, тип: Fixed Port
Общ брой портове: 54
Основни портове, тип: 48x RJ45 10/100/1000Mb 802.3at (up to 30W) PoE auto- sensing ports
Power Over Ethernet (PoE): 802.3at (30W) PoE
Uplink портове: 4x 10G SFP+
Свободни (10GB) слотове: -
Управление: CLI, Web, SNMP; 1x 10/100/1000BaseT Ethernet management port
Stackable: 2x 100G QSFP28
Fans: 3 pluggable fan modules; Normal airflow only
Захранване: 1x 1050W AC PSU included; 2 pluggable AC PSUs — 1 default and 1 optional or 2 optional DC PSUs; 1 EPS (optional and conected from MPS-1S or MPS-3S power shelf)
Routing: Line-rate Layer 3 routing (Static routes: 1024 (IPv4)/1024 (IPv6); Dynamic routes: 8158 (IPv4)/4096 (IPv6); RIP routing interfaces: 512, VLAN routing interfaces: 128)
Памет (Flash, RAM): 4 GB DDR4 SO-DIMM, 8 GB mSATA 2.0/M.2 SSD
Капацитет за маршрутизиране/превключване, Gbps: 576 Gbps
Пропускателна способност, Mpps: 800 Mpps
MAC адреси: 32K
VLAN (брой, стандарти): Private VLAN extensions and Private VLAN Edge support; VLAN routing interfaces: 128; VLANs supported: 4094; Protocol-based VLANs: Supported; Max VLAN interfaces with ACLs applied: 24
QoS: DiffServ Field, DiffServ Architecture, Assured Fwd PHB, Port Based QoS Services (TCP/UDP) Mode, Red/WRED, Flow Based QoS Services, Audio Video Bridging Mode (IPv4/IPv6), UDLD, srTCM, trTCM
L2 мрежови стандарти: 802.3ab 802.1ax (Layer 2) 802.1d, 802.1w, 802.1s, 802.1x (Mgmt/Security), 802.3x (Layer 2) 802.3 802.3ba (40 GbE and 100 GbE) 802.3bt 802.3at 802.3az 802.1v 1613 802.1p, 1q 802.1s 802.3u, 802.3bz, 802.3at

L3 мрежови стандарти: RIP, OSPF, VRRP, MIB
IPv6 functionality: Layer 3 Advanced IPv4 and IPv6 functionality including BGP, VRF, BFD, PIM-SM/DM/SSM, IGMP/MLD, RIPv1/v2, OSPFv2/v3
Сигурност: RADIUS, TACACS+, 802.1x
Размери (Ш, Д, В), mm: 434 x 400 x 43.5 mm
Опция за монтаж: Rackmount, 1U
Други: 1x Micro USB Type-B console port, 1x USB Type-A port, 1x RJ45 serial console port; Two-core Denverton-NS CPU

Цена : 7548.00 EUR с ДДС

Наличност: Този продукт е бил добавен в нашия каталог на Пт 29 май, 2026

November 21, 2026, 12:12