

МРЕЖОВА ТЕХНИКА > СУИЧОВЕ

D-Link 24x10G SFP+ ports + 4x10G Base-T ports Smart Managed Switch



Модел : DXS-1210-28S

D-Link 24x10G SFP+ ports + 4x10G Base-T ports Smart Managed Switch

Суич, тип: Fixed Port

Общ брой портове: 28

Основни портове, тип: 24x 10G SFP+ ports

Power Over Ethernet (PoE): No

Uplink портове: 4x 10GBASE-T ports

Свободни (10GB) слотове: No

Управление: Web-based GUI, D-Link Network Assistant Utility, Full CLI, Telnet Server, TFTP Client, Configurable MDI/MDIX, SNMP, SNMP Trap, Smart Wizard. LLDP, LLDP-MED, ICMP, DHCP, System Log, BootP/DHCP Client, SNTIP

Stackable: No

Fans: 2x Smart Fan

Захранване: AC Input: 100 to 240 VAC, Max Power

Consumption: 87.3 W

Routing: Static (Max. 64 IPv4 entries, Max. 64 IPv6 entries)

Памет (Flash, RAM): -

Капацитет за маршрутизиране/превключване, Gbps: 560 Gbps

Пропускателна способност, Mpps: 416.64 Mpps

MAC адреси: Up to 32K entries, Static MAC Addresses: 256

VLAN (брой, стандарти): 802.1Q VLAN, Port-based VLAN,

Configurable VID: 1~4094, Voice VLAN, Auto Surveillance

VLAN, Asymmetric VLAN, 4K VLAN Groups

QoS: CoS based on: Switch port, 802.1p Priority Queues, DSCP, ToS, IPv6 Traffic Class, TCP/UDP port, MAC Address, Ether Type, IP Address, Protocol Type, IPv6 Flow Label/Traffic Class, 802.1p Priority Queue, 8 queues per port, Queue Handling, Bandwidth Control

L2 мрежови стандарти: IEEE 802.3u 100BASE-TX FE, IEEE 802.3ab 1000BASE-T GE, IEEE 802.3az Energy Efficiency Ethernet (EEE), IEEE 802.3an 10GBASE-T 10 GE, IEEE 802.3ae 10GbE over fiber, IEEE 802.3z 1000BASE-X, Auto MDI/MDIX support for 1000/10GBASE-T

IPv6 functionality: Supports 8 IPv4 and 8 IPv6 interfaces, IPv6 Neighbor Discovery (ND), IPv6 Traffic Class, IPv6 flow label, IPv6 Snooping, IPv6 Source Guard, DHCPv6 Guard, IPv6 ND Inspection, IPv6 Route Advertisement (RA) Guard, Support IPv4/ IPv6 SSL/SSH

Сигурност: Broadcast/Multicast/Unicast Storm Control,



D-Link Safeguard Engine, DHCP Server Screening,
IP-MAC-Port Binding, Traffic Segmentation, SSH, SSL, ARP
Spoofing Prevention, DoS Attack Prevention, Port Security,
Duplicate Address Detection

Размери (Ш, Д, В), mm: 441 x 209.5 x 44 mm

Опция за монтаж: Rackmount

Други: RJ45 console port, Auto MDI/MDIX adjustment for all
twisted-pair ports

Цена : 2344.55 EUR с ДДС

Наличност: Този продукт е бил добавен в нашия каталог на Пт 31 юли, 2026