

МРЕЖОВА ТЕХНИКА > СУИЧОВЕ

## Cisco CBS220 Smart 8-port GE, PoE, Ext PS, 2x1G SFP



Модел : CBS220-8P-E-2G-EU

Cisco CBS220 Smart 8-port GE, PoE, Ext PS, 2x1G SFP

Суич, тип: Fixed Port

Общ брой портове: 10

Основни портове, тип: 8x10/100/1000Base-T

Power Over Ethernet (PoE): Support 802.3af, 802.3at, and Cisco pre-standard (legacy) PoE with maximum power of 30 W per port; PoE Power Budget: 65 W; 8 Ports That Support PoE

Uplink портове: 2x1G SFP

Свободни (10GB) слотове: -

Управление: Business Dashboard and mobile app., Network Plug and Play (PnP) agent, Web user interface, Text-editable config files, Scriptable CLI, SNMP, MIB, Remote Monitoring (RMON), DHCP, Other

Stackable: -

Fans: Fanless

Захранване: External (100-240 V, 50-60 Hz)

Routing: -

Памет (Flash, RAM): Flash: 64 MB; CPU memory: 256 MB;

Packet Buffer: 4.1 Mb

Капацитет за маршрутизиране/превключване, Gbps: 20 Gbps

Пропускателна способност, Mpps: 14.88 Mpps

MAC адреси: Up to 8 192 Media Access Control (MAC) addresses

VLAN (брой, стандарти): up to 256 VLANs simultaneously; Port-based and 802.1Q tag-based VLANs; Management VLAN; Guest VLAN; Auto voice VLAN; QinQ VLAN; Generic VLAN Registration Protocol (GVRP) and Generic Attribute Registration Protocol (GARP)

QoS: 8 hardware queues per port; Strict priority and WRR queue assignment based on DSCP and Port-based class of service (802.1p/CoS); 802.1p VLAN priority-based; IPv4/v6 IP precedence, ToS, DSCP-based, DiffServ; classification and re-marking ACLs, trusted QoS

L2 мрежови стандарти: IEEE 802.3, IEEE

802.3u/ab/ad/z/x/af/at; IEEE 802.1D (STP, GARP, and GVRP), IEEE 802.1Q/p VLAN, IEEE 802.1w RSTP, IEEE 802.1s Multiple STP, IEEE 802.1X; RFC

L3 мрежови стандарти: -

IPv6 functionality: IPv6 host mode, IPv6 over Ethernet,

IPv6/IPv4 Dual Stack, IPv6 neighbor and router discovery

(ND), IPv6 stateless address auto-configuration, MTU discovery, DAD, ICMP; ACL; MLD; applications  
Сигурност: ACLs, Port security, IEEE 802.1X (authenticator role); RADIUS, TACACS+; MAC address filtering; Storm control; DoS protection; BPDU Guard; Spanning Tree Loop Guard; SSH, SSL  
Размери (Ш, Д, В), mm: 279 x 170 x 44 mm  
Опция за монтаж: Rackmount

Цена : 150.19&nbsp;EUR с ДДС

*Наличност: Този продукт е бил добавен в нашия каталог на Чт 12 ноември, 2026*