МОНИТОРИ И ТЕЛЕВИЗОРИ > МОНИТОРИ

HP P22H G4 FHD Height Adjust Monitor 21.5inch Anti-Glare IPS Black 16:9 1920x1080 60Hz 5ms 178/178 250 nits 1000:1 102 PPI



Модел : 3674621
HP P22H G4 FHD Height Adjust Monitor 21.5inch Anti-Glare IPS Black 16:9 1920x1080 60Hz 5ms 178/178 250 nits 1000:1 102 PPI
HP P22H G4 FHD Height Adjust Monitor 21.5inch Anti-Glare IPS Black 16:9 1920x1080 60Hz 5ms 178/178 250 nits 1000:1 102 PPI
B B
ManufacturerHP INC.
Manufacturer Part No7UZ36AA#ABB
B

Product Features
пїS Security lock ready yesпїS Detachable basепїS Low blue light modesпїS LED backlighting
General
Display TypeLED-backlit LCD monitor / TFT active matrix
Energy ClassClass E
Energy Consumption per Year21 kWh
Diagonal Size22"
Viewable Size21.5"
Panel TypeIPS
Aspect Ratio16:9
Native ResolutionFull HD (1080p) 1920 x 1080 at 75 Hz
Pixel Pitch0.247 mm
Pixel Per Inch102
Brightness250 cd/mBl
Contrast Ratio1000:1 / 8000000:1 (dynamic)
Colour Gamut72% NTSC
Response Time5 ms (grey-to-grey)
Vertical Refresh Rate48 - 75 Hz
Horizontal Refresh Rate30 - 86 kHz
Horizontal Viewing Angle178
Vertical Viewing Angle178
Screen CoatingAnti-glare
Backlight TechnologyLED backlight
Colour Temperature9300K, 5000K, 6500K
FeaturesHDCP, Low Blue Light Mode, Flicker Free technology, Color Calibrated, 3-sided micro-edge, 6-bit + A-FRC Color Depth, 72% NTSC colour gamut
ColourBlack
Dimensions (WxDxH)49.73 cm x 21.16 cm x 45.49 cm - with stand

March 29, 2024, 2:42 pm

Weight4.14 kg
Connectivity
InterfacesDisplayPort (HDCP) HDMI (HDCP) VGA
Mechanical
Display Position AdjustmentsHeight, pivot (rotation), swivel, tilt
Tilt Angle-5/+23
Swivel Angle360
Rotation Angle180
Height Adjustment100 mm
VESA Mounting Interface100 x 100 mm
Miscellaneous
FeaturesSecurity lock slot (cable lock sold separately), arsenic free, mercury free
Cables Included1 x VGA cable - 1.8 m
Backlight Life30,000 hours
Compliant StandardsPlug and Play, CSA, UL, VCCI, BSMI, NOM, TUV S, WHQL, CB, CCC, PSB, FCC, RoHS, ISO 9241-307, KCC, WEEE, ICES, MEPS, KC, CEL, EAC, CEL Grade 1, ISC, CP65, low halogen, DisplayPort 1.2, IEEE 1680, ISO 11469, ISO 1043
LocalisationEnglish / Europe
Security Slot TypeKensington security slot
Power
Input VoltageAC 120/230 V (50/60 Hz)
Power Consumption (On mode)14 W
Power Consumption SDR (On mode)14 kWh/1000h
Power Consumption (Typical)19 Watt
Power Consumption Stand by0.3 Watt
On / Off SwitchNo
Software / System Requirements
Included SoftwareHP Display Assistant
Dimensions & Weight
Dimensions & Weight DetailsWith stand - width: 49.73 cm - depth: 21.16 cm - height: 45.49 cm - weight: 4.14 kg Without stand - width: 49.73 cm - depth: 4.59 cm - height: 30.11 cm - weight: 2.06 kg
Dimensions & Weight (Shipping)
Shipping Width56.7 cm
Shipping Depth18.9 cm
Shipping Height38.5 cm
Shipping Weight5.65 kg
Environmental Standards
TCO CertifiedTCO Certified Displays 8
ENERGY STAR CertifiedYes
ENERGY STAR Version8.0
Manufacturer Warranty

March 29, 2020 2:42 am

Service & SupportLimited warranty - 3 years
Environmental Parameters
Min Operating Temperature5 B°C
Max Operating Temperature35 B°C
Humidity Range Operating20 - 80% (non-condensing)

Technical data provided by third party. We assume no liability for errors within these data.

Цена : 0.00лв с ДДС

Наличност: Този продукт е бил добавен в нашия каталог на Fri 28 January, 2022

March 29, 2024, 2:42 am