

КОМПЮТРИ И СЪРВЪРИ > Сървъри

## **Dell PowerEdge R750XS, Chassis 16x2.5" SAS, SATA, Dual Intel Xeon Silver 4310, 64GB, 2x600GB HD SAS ISE 12Gbps 10k 512n 2.5" HP, Rails, Bezel, Broadcom 57412 Dual Port 10GbE SFP, PERC H755, iDRAC9 Enterprise 15G, Dual PS Redundant 800W, 3Y Basic Onsite**



Модел : PER750XS9A

Dell PowerEdge R750XS, Chassis 16x2.5" SAS, SATA, Dual Intel Xeon Silver 4310, 64GB, 2x600GB HD SAS ISE 12Gbps 10k 512n 2.5" HP, Rails, Bezel, Broadcom 57412 Dual Port 10GbE SFP, PERC H755, iDRAC9 Enterprise 15G, Dual PS Redundant 800W, 3Y Basic Onsite  
Серия: PowerEdge R750XS

Процесор: 2x Intel Xeon Silver 4310, 2.10GHz, 12C/24T, 18 MB Cache, 120 W

Памет, GB: 64 GB

Памет, слотове: 16 DDR4 DIMM slots, supports RDIMM 1 TB max, speeds up to 3200 MT/s; Supports registered ECC DDR4 DIMMs only

Твърд диск, GB: 2x 600GB Hard Drive SAS ISE 12Gbps 10k 512n 2.5in Hot-Plug

Дисков контролер: PERC H755

Брой поддържани дискове: 16x 2.5" (SFF) SAS/SATA

Оптично устройство: -

Мрежа: Broadcom 57412 Dual 10GbE SFP, 2x 1 GbE LOM

Разширителен слот: Up to 5 x PCIe Gen4 slots: 1x PCIe Gen3 slots, 3x16 Gen4 low profile, 2x16 Gen4 low profile (optional), 1x 8 Gen3 (x4 lane) low profile

Интерфейс: Front: 1x iDRAC Direct (Micro-AB USB) port, 1x USB 2.0, 1x VGA; Rear: 1x USB 2.0, 1x Serial (optional), 1x USB 3.0, 2x Ethernet, 1x VGA; Internal: 1x USB 3.0 (optional)

Порт за отдалечено управление: yes

Захранване: 1400W

Съвместими операционни системи: Canonical Ubuntu Server LTS, Citrix Hypervisor, Microsoft Windows Server with Hyper-V, Red Hat Enterprise Linux, SUSE Linux Enterprise Server, VMware ESXi

Софтуер за управление: iDRAC9 Enterprise 15G

Форм-фактор: 2U Rack

Тип на шасито: Hot-Plug

Други: Rails, Bezel

Цена : 5782.60&nbsp;EUR с ДДС



*Наличност: Този продукт е бил добавен в нашия каталог на Пн 08 юни, 2026*

*April 9, 2026, 2:50 am*