
*МРЕЖОВА ТЕХНИКА > СУИЧОВЕ*

# Dell Networking S3124P, L3, PoE+, 24x 1GbE, 2x Combo, 2x 10GbE SFP+ fixed ports, Stacking, IO to PSU air, 1x 715w AC PS, 1Y PS NBD, 210-AIMO



Модел : DNS3124P
Dell Networking S3124P, L3, PoE+, 24x 1GbE, 2x Combo, 2x 10GbE SFP+ fixed ports, Stacking, IO to PSU air, 1x 715w AC PS, 1Y PS NBD, 210-AIMO
Суич, тип: Fixed Port
Общ брой портове: 24x RJ45 auto-sensing (1Gb/100Mb/10Mb) PoE+ fixed ports
Основни портове, тип: 10GE SFP + dedicated ports
Power Over Ethernet (PoE): PoE+ standard
Uplink портове: 2x10GE SFP
Свободни (10GB) слотове: Hot swappable expansion module supporting dual-port SFP+ or dual-port 10GBaseT
Управление: 1 RJ45 console/management port with RS232 signaling
Stackable: Yes
Fans: Redundant variable speed fans
Захранване: 1x 715 W PSU included
Routing: Layer 3 Advanced
Памет (Flash, RAM): 256 MB
Капацитет за маршрутизиране/превключване, Gbps: 212 Gbps
Пропускателна способност, Mpps: 158 Mpps
MAC адреси: 56K (80K in L2 scaled mode)
VLAN (брой, стандарти): 802.1Q VLAN Tagging, Double VLAN Tagging, GVRP, 802.3ac Frame Extensions for VLAN Tagging
QoS: 8 priority queues per port
L2 мрежови стандарти: IEEE compliance: 802.1AB, 802.1D, 802.1p, 802.1Q, 802.1Qbb, 802.1Qaz, 802.1s, 802.1w, 802.1x, 802.1x-2010, 802.3ab, 802.3ac, 802.3ad, 802.1ax, 802.3ae, 802.3af, 802.3at, 802.3az, 802.3u, 802.3x, 802.3z
IPv6 functionality: All protocols, including IPv4 and IPv6
Сигурност: TACACS+ accounting and RADIUS
Размери (Ш, Д, В), mm: 407 x 434 x 44
Опция за монтаж: Rackmount
Други: 1x RJ45 console/management port with RS232 signaling (RJ-45 to female DB-9 connector cable included), Out-of-band management port (10/100/1000BASE-T)  USB (Type A) port for configuration via USB flash drive

## Цена : 4188.00 EUR с ДДС

*Наличност: Този продукт е бил добавен в нашия каталог на  Вт 28 юли, 2026*

November 22, 2026, 7:03 a