

МРЕЖОВА ТЕХНИКА > СУИЧОВЕ

ZyXEL GS2220-28HP, EU region, 24-port GbE L2 PoE Switch with GbE Uplink (1 year NCC Pro pack license bundled)



Модел : GS2220-28HP-EU0101F

ZyXEL GS2220-28HP, EU region, 24-port GbE L2 PoE Switch with GbE Uplink (1 year NCC Pro pack license bundled)

Суич, тип: Fixed Port

Общ брой портове: 28

Основни портове, тип: 24x 100/1000Base-T

Power Over Ethernet (PoE): High power PoE 802.3at, 24 PoE ports (up to 375W total)

Uplink портове: 4x Combo 1000BaseT/SFP ports

Свободни (10GB) слотове: No

Управление: Cloud management by Nebula Control Center, New for V4.70 Networked AV mode by Web Interface, Zyxel iStacking™, Web interface, Management through Web interface, Console, Telnet, SNMP, Multilevel CLI, CLI, DHCP

Stackable: No

Fans: -

Захранване: Internal (100 to 240 V AC, 50/60 Hz)

Routing: -

Памет (Flash, RAM): 32 MB/256 MB

Капацитет за маршрутизиране/превключване, Gbps: 56

Gbps

Пропускателна способност, Mpps: 42 Mpps

MAC адреси: 16000 MAC address table size

VLAN (брой, стандарти): 802.1Q static VLANs/dynamic

VLANs: 1 K/4 K; Port-based/Protocol-based/IP

subnet-based/MAC-based/Private/Voice/Vendor ID based

VLAN, VLAN ingress filtering, MVR

QoS: 8 queues per port, Storm control and event log:

Broadcast, multicast, unknown unicast (DLF), Port-based

rate limiting (ingress/ egress), Rate limiting per IP/TCP/UDP

per port, Policy-based rate limiting , 802.3x flow control,

802.1p Class of Service, DSCP

L2 мрежови стандарти: IEEE 802.3u, IEEE 802.3ab, IEEE

802.3z, IEEE 802.3af PoE, IEEE 802.3at PoE plus, IEEE

802.3az EEE, IEEE 802.3x flow contro, • IEEE 802.1ab

LLDP/LLDP-MED, IEEE 802.3ad, IEEE 802.1d, IEEE 802.1w,

IEEE 802.1s, IEEE 802.1Q, IEEE 802.1p

L3 мрежови стандарти: -

IPv6 functionality: IPv6 over Ethernet, IPv6 addressing

architecture, Dual stack, ICMPv6, Path MTU, Minimum path

MTU size of 1280, Encapsulation for maximum PMTU of 1500

, Neighbor discovery, DHCPv6 relay, DHCP client IPv6, DHCP



snooping IPv6

Сигурност: Port security, Layer 2 MAC filtering, Layer 3 IP filtering, Layer 4 TCP/UDP socket filtering, Static MAC forwarding, RADIUS, TACACS+, SSH v2, SSL, DHCP, Policy-based security filtering, Port isolation and etc.

Размери (Ш, Д, В), mm: 441 x 270 x 44

Опция за монтаж: Rackmount

Цена : 520.81 EUR с ДДС

Наличност: Този продукт е бил добавен в нашия каталог на Чт 06 август, 2026