МРЕЖОВА ТЕХНИКА > СУИЧОВЕ

ZyXEL XGS2220-30HP, L3 Access Switch, 400W PoE, 16xPoE+/10xPoE++, 24x1G RJ45 2x10mG RJ45, 4x10G SFP+ Uplink, incl. 1 yr NebulaFlex Pro



Модел : XGS2220-30HP-EU0101F
ZyXEL XGS2220-30HP, L3 Access Switch, 400W PoE, 16xPoE+/10xPoE++, 24x1G RJ45 2x10mG RJ45, 4x10G SFP+ Uplink, incl. 1 yr NebulaFlex Pro
Суич, тип: Fixed Port, Layer 3 Access
Общ брой портове: 30
Основни портове, тип: 24x1G RJ45 (100/1000 Mbps) + 2x10mG RJ45 (100M/1G/2.5G/5G/10G Ethernet)
Power Over Ethernet (PoE): 26 PoE ports: 16x Gigabit RJ-45 PoE+ ports + 8x Gigabit RJ-45 PoE++ (60 W) ports + 2x 10G Multi-Gigabit (1G/2.5G/5G/10G) RJ-45 PoE++ (60 W) ports
Uplink портове: 4xSFP+
Свободни (10GB) слотове: -
Управление: Standalone management by Web interface; Cloud management by Nebula Control Center; Management through Console, Telnet, SNMP; Multilevel CLI; DHCP
Stackable: Physical stacking (In the future firmware release)
Fans: 1 x smart fan
Захранване: 100 - 240 V AC, 50/60 Hz; Max. power consumption: 37.62W
Routing: Static; Static route: 64
Памет (Flash, RAM): 64 MB/1 GB (Flash/RAM)
Капацитет за маршрутизиране/превключване, Gbps: 168 Gbps
Пропускателна способност, Mpps: 125 Mpps
MAC адреси: 32 K
VLAN (брой, стандарти): 802.1Q static VLANs/dynamic VLANs: 4 K/4 K; VLAN isolation; Port-based/Vendor ID based/Protocol-based/IP subnet-based/MAC-based/Private/Voice VLAN; Independent VLAN Learning (IVL); VLAN Translation/trunking/mapping; QinQ; GVRP; L2PT
QoS: No. of hardware queues per port (Standalone/stacking): 8*/6; Storm control and event log; Port-based rate limiting; Rate limiting per IP/TCP/UDP per port; Policy-based rate limiting; 802.3x flow control; 802.1p Class of Service; DSCP
L2 мрежови стандарти: IEEE 802.3z, IEEE 802.3ab, IEEE 802.3an, IEEE 802.3ae, IEEE 802.1X
L3 мрежови стандарти: IEEE 802.1D Spanning Tree Protocol (STP); IEEE 802.1w Rapid Spanning Tree Protocol

(RSTP); IEEE 802.1s Multiple Spanning Tree Protocol (MSTP); IEEE 802.3ad LACP
IPv6 functionality: Max. 1 K IPv4 entries; Max. 512 IPv6 entries; IP source guard (IPv4*/IPv6); ACL packet filtering (IPv4/IPv6); Syslog (IPv4/IPv6); IPv6 over Ethernet (RFC 2464); IPv6 addressing architecture (RFC 4291); IPv6 binding- static/dynamic
Сигурност: Port security; Layer 2 MAC filtering; Layer 3 IP filtering; Layer 4 TCP/UDP socket filtering; Static MAC forwarding; RADIUS; TACACS+; SSH v2; SSL; DHCP;
Размери (Ш, Д, В), mm: 441 x 330 x 44 mm
Опция за монтаж: Rackmount
Други: Rack mounting kit included

Цена : 721.06 EUR с ДДС

Наличност: Този продукт е бил добавен в нашия каталог на Чт 17 декември, 2026