


МРЕЖОВА ТЕХНИКА > СУИЧОВЕ

## Cisco Catalyst 1300 16-port GE, PoE, 4x10G SFP+



Модел : C1300-16P-4X

Cisco Catalyst 1300 16-port GE, PoE, 4x10G SFP+

Суич, тип: Fixed Port

Общ брой портове: 20

Основни портове, тип: 16x 10/100/1000Base-T PoE+ ports with 120W power budget

Power Over Ethernet (PoE): PoE+ (120W), 48 ports; 802.3at PoE+, 802.3af

Uplink портове: 4x SFP+

Свободни (10GB) слотове: -

Управление: Cisco Business Dashboard; Cisco Business mobile app; Cisco Network Plug and Play (PnP) agent; Web user interface; SNMP; MIB; RMON; RSPAN; sFlow agent; DHCP; SCP; CLI; Other management Traceroute, single IP management, HTTP/HTTPS, SSH, RADIUS and etc.

Stackable: Up to 8 switches in a stack. Up to 200 ports managed as a single system with hardware failover

Fans: Fanless

Захранване: 100-240V 50-60 Hz, internal, universal

Routing: Dynamic Layer 3 routing

Памет (Flash, RAM): 512 MB (Flash), 1 GB DDR4 (DRAM), 1.5 MB (Packet buffer)

Капацитет за маршрутизиране/превключване, Gbps: 112 Gbps

Пропускателна способност, Mpps: 83.32 Mpps

MAC адреси: 16 000 addresses

VLAN (брой, стандарти): Support for up to 4093 VLANs simultaneously; Port-based and 802.1Q tag-based VLANs, MAC-based VLAN, protocol-based VLAN, IP subnet-based VLAN; Management VLAN;

Private/Guest/unauthenticated/Auto

surveillance/CPE/Voice/Dynamic/Multicast TV VLAN

QoS: 8 hardware queues; Strict priority and WRR;

Port-based, 802.1p VLAN priority-based, IPv4/v6 IP

precedence/Type of Service (ToS)/DSCP-based,

Differentiated Services (DiffServ), classification and

remarking ACLs, trusted QoS Queue assignment based on

DSCP

L2 мрежови стандарти: IEEE 802.3, IEEE

802.3u/ab/ad/z/x/af/at; IEEE 802.1D (STP)/1Q/p VLAN/w

RSTP/s Multiple STP/X Port Access Authentication; RFC

IPv6 functionality: IPv6 host mode, IPv6 over Ethernet, dual

IPv6/IPv4 stack; IPv6 neighbor and router discovery (ND);

DAD, ICMP; DHCPv6; IPv6 over IPv4 network with ISATAP tunnel support; IPv6 QoS; ACL; First Hop Security; MLD  
Сигурност: SSH, SSL, IEEE 802.1x (authenticator role):RADIUS authentication and accounting, MD5 hash, guest VLAN, unauthenticated VLAN, single/multiple host mode, and single/multiple sessions; MAC/Web-based authentication; STP; DHCP; IPSG; DAI; IPMB; SCT; SSD; ACLs  
Размери (Ш, Д, В), mm: 268 x 297 x 44 mm  
Опция за монтаж: Rackmount

Цена : 664.92&nbsp;EUR с ДДС

*Наличност: Този продукт е бил добавен в нашия каталог на Пт 11 септември, 2026*