

КОМПЮТРИ И СЪРВЪРИ > Сървъри

Dell PowerEdge R7515 Server, 3.5" Chassis 12 Hot Plug, AMD EPYC 7443P 2.85GHz 24C/48T 128M Cache, 2x 32GB RDIMM 3200MT/s, PERC H730P 2GB NV Cache, 480GB SSD RI, Dual 750W Titanium PSU, Riser 2(2x16FH+2x16LP PCIe), iDRAC9 Express, 3Y ProSupport NBD



Модел : #Q0016010033717

Dell PowerEdge R7515 Server, 3.5" Chassis 12 Hot Plug, AMD EPYC 7443P 2.85GHz 24C/48T 128M Cache, 2x 32GB RDIMM 3200MT/s, PERC H730P 2GB NV Cache, 480GB SSD RI, Dual 750W Titanium PSU, Riser 2(2x16FH+2x16LP PCIe), iDRAC9 Express, 3Y ProSupport NBD
Серия: PowerEdge R7515

Процесор: AMD EPYC 7443P 2.85 GHz, 24C/48T, 128MB L3 Cache, 165-200W

Памет, GB: 2x 32GB RDIMM 3200MT/s

Памет, слотове: 16 slots 288-pin

Твърд диск, GB: 480GB SSD

Дисков контролер: PERC H730P RAID Controller, 2GB NV Cache, Mini card

Брой поддържани дискове: 3.5" Chassis with up to 12 Hot Plug Hard Drives

Оптично устройство: -

Мрежа: PowerEdge R6515/R7515 Motherboard, with 2 x 1Gb Onboard LOM (BCM5720)

Разширителен слот: PCIe Up to 4: 2 Gen3 slots (1 x8; 1 x16), 2 Gen4 slots (2 x16); Riser 2(2x16FH+2x16LP PCIe)

Интерфейс: Front Ports: 1 Dedicated iDRAC direct micro-USB, 2 USB 2.0, 1 Video; Rear Ports: 2 1GbE, 1 Dedicated iDRAC network port, 1 Serial, 2 USB 3.0, 1 Video

Порт за отдалечено управление: yes

Захранване: Dual 750W Titanium PSU

Съвместими операционни системи: Canonical Ubuntu Server LTS, Citrix Hypervisor, Microsoft Windows Server with Hyper-V, Red Hat Enterprise Linux, SUSE Linux Enterprise Server, VMware ESXi

Софтуер за управление: iDRAC9 Enterprise 15G

Форм-фактор: 2U Rack

Тип на шасито: Hot-Plug

Други: Rails, Bezel

Цена : 6000.00 EUR с ДДС

Наличност: Този продукт е бил добавен в нашия каталог на Ср 04 март, 2026