

КОМПЮТЪРНИ КОМПОНЕНТИ > Дънни Платки  
**GB Z790 AORUS MASTER X**



Модел : GB Z790 AORUS MASTER X /1700

GB Z790 AORUS MASTER X

CPU's supported: LGA1700 socket: Support for the 14th, 13th, and 12th Generation Intel® Core™, Pentium® Gold and Celeron® Processors\*; L3 cache varies with CPU

Memory type: Support for DDR5 8266(O.C.) / 8200(O.C.) / 8000(O.C.) / 7950(O.C.) / 7900(O.C.) / 7800(O.C.) / 7600(O.C.) / 7400(O.C.) / 7200(O.C.) / 7000(O.C.) / 6800(O.C.) / 6600(O.C.) / 6400(O.C.) / 6200(O.C.) / 6000(O.C.) / 5800(O.C.) / 5600(O.C.) / 5400(O.C.) / 5200(O.C.) / 4800 / 4000 MT/s memory modules; 4 x DDR5 DIMM sockets

supporting up to 192 GB (48 GB single DIMM capacity) of system memory Dual channel memory architecture; Support for ECC Un-buffered DIMM 1Rx8/2Rx8 memory modules (operate in non-ECC mode); Support for non-ECC Un-buffered DIMM 1Rx8/2Rx8/1Rx16 memory modules;

Support for Extreme Memory Profile (XMP) memory modules  
Chipset: Intel® Z790 Express Chipset

Graphics: Integrated Graphics Processor-Intel® HD Graphics support: - 1 x DisplayPort, supporting a maximum resolution of 4096x2304@60 Hz

Expansion Slots: CPU: - 1 x PCI Express x16 slot, supporting PCIe 5.0 and running at x16 (PCIEX16); \* The PCIEX16 slot shares bandwidth with the M2C\_CPU connector. The PCIEX16 slot operates at up to x8 mode when a device is installed in the M2C\_CPU connector.; \* For optimum performance, if only one PCI Express graphics card is to be installed, be sure to install it in the PCIEX16 slot.; Chipset: - 1 x PCI Express x16 slot, supporting PCIe 3.0 and running at x4 (PCIEX4); - 1 x PCI Express x16 slot, supporting PCIe 3.0 and running at x1 (PCIEX1)

Storage: CPU: - 1 x M.2 connector (Socket 3, M key, type 25110/2280 PCIe 5.0 x4/x2 SSD support) (M2C\_CPU); - 1 x M.2 connector (Socket 3, M key, type 22110/2280 PCIe 4.0 x4/x2 SSD support) (M2A\_CPU); Chipset: - 1 x M.2 connector (Socket 3, M key, type 22110/2280 PCIe 4.0 x4/x2 SSD support) (M2Q\_SB); - 1 x M.2 connector (Socket 3, M key, type 2280 PCIe 4.0 x4/x2 SSD support)(M2P\_SB); - 1 x M.2 connector (Socket 3, M key, type 2280 SATA and PCIe 4.0 x4/x2 SSD support) (M2M\_SB); - 4 x SATA 6Gb/s connectors; RAID 0, RAID 1, RAID5, and RAID 10 support for NVMe SSD storage devices; RAID 0, RAID 1, RAID5, and RAID 10

support for SATA storage devices

I/O: 1 x Q-Flash Plus button; 1 x Clear CMOS button; 2 x SMA antenna connectors (2T2R); 1 x DisplayPort; 1 x USB Type-C® port, with USB 3.2 Gen 1 support; 2 x USB Type-C® ports, with USB 3.2 Gen 2x2 support; 7 x USB 3.2 Gen 2 Type-A ports (red); 4 x USB 3.2 Gen 1 ports; 1 x RJ-45 port; 1 x optical S/PDIF Out connector; 2 x audio jacks  
Connectors: 1 x 24-pin ATX main power connector; 2 x 8-pin ATX 12V power connectors; 1 x CPU fan header; 1 x CPU fan/water cooling pump header; 4 x system fan headers; 4 x system fan/water cooling pump headers; 3 x addressable RGB Gen2 LED strip headers; 1 x RGB LED strip header; 5 x M.2 Socket 3 connectors; 4 x SATA 6Gb/s connectors; 1 x front panel header; 1 x front panel audio header; 1 x USB Type-C® header, with USB 3.2 Gen 2x2 support; 2 x USB 3.2 Gen 1 headers; 2 x USB 2.0/1.1 headers; 1 x noise detection header; 2 x Thunderbolt® add-in card connectors; 1 x Trusted Platform Module header (For the GC-TPM2.0 SPI/GC-TPM2.0 SPI 2.0/GC-TPM2.0 SPI V2 module only); 1 x power button; 1 x reset button; 1 x reset jumper; 1 x Clear CMOS jumper; 2 x temperature sensor headers;

Voltage Measurement Points

Audio: Realtek® ALC1220-VB CODEC; \* The front panel line out jack supports DSD audio.; ESS ES9118 DAC chip; Support for DTS:X® Ultra; High Definition Audio;

2/4/5.1-channel; Support for S/PDIF Out

LAN: Marvell® AQtion AQC113C 10GbE LAN chip (10 Gbps/5 Gbps/2.5 Gbps/1 Gbps/100 Mbps)

BIOS: 1 x 256 Mbit flash; Use of licensed AMI UEFI BIOS; PnP 1.0a, DMI 2.7, WfM 2.0, SM BIOS 2.7, ACPI 5.0

Form Factor: E-ATX Form Factor; 30.5cm x 26.0cm

OS: Support for Windows 11 64-bit

Other: Qualcomm® Wi-Fi 7 QCNCM865 (PCB rev. 1.0); - 802.11a, b, g, n, ac, ax, be, supporting 2.4/5/6 GHz carrier frequency bands; - BLUETOOTH 5.3; - Support for 11be 320MHz wireless standard; MediaTek Wi-Fi 7 MT7927, RZ738 (PCB rev. 1.1); - 802.11a, b, g, n, ac, ax, be, supporting 2.4/5/6 GHz carrier frequency bands; - BLUETOOTH 5.3; - Support for 11be 320MHz wireless standard; Intel® Wi-Fi 7 BE200 (PCB rev. 1.2); - 802.11a, b, g, n, ac, ax, be, supporting 2.4/5/6 GHz carrier frequency bands; - BLUETOOTH 5.3; - Support for 11be 320MHz wireless standard; (Actual data rate may vary depending on environment and equipment.); Note: Wi-Fi 7 features require Windows 11 SV3 to function properly. (There is no support driver for Windows 10); Wi-Fi 7 channels on 6GHz band availability depends on individual country's regulations.



Warranty: 36 Months

Цена : 590.18&nbsp;EUR с ДДС

*Наличност: Този продукт е бил добавен в нашия каталог на Пт 15 май, 2026*