ОХРАНИТЕЛНА ТЕХНИКА > IP Видео Камери

HikVision 2 MP ColorVu Fixed Turret Network Camera, 2.8 mm, 24/7 colorful imaging, White LED light up to 30m, 120 dB WDR, 3D DNR, H.265+, IP67, Built-in microphone, Built-in memory card slot up to 512 GB, 12Vdc/PoE 7W



Модел : DS-2CD2327G2-LU(C)
HikVision 2 MP ColorVu Fixed Turret Network Camera, 2.8 mm, 24/7 colorful imaging, White LED light up to 30m, 120 dB WDR, 3D DNR, H.265+, IP67, Built-in microphone, Built-in memory card slot up to 512 GB, 12Vdc/PoE 7W
Тип: IP
Сензор, тип: CMOS
Размер на оптичния сензор: 1/2.8" Progressive Scan CMOS
Резолюция, MP: 2 MP
Фокално разстояние: 2.8 mm, horizontal FOV 107°, vertical FOV 56°, diagonal FOV 127°
Минимална осветеност, lx: 0.0005 Lux @ (F1.0, AGC ON), 0 Lux with Light
IR осветление: White LED light up to 30m
Максимална резолюция, pixels: 1920x1080
Формати на компресиране: Main stream: H.265+/H.265/H.264+/H.264; Sub-stream: H.265/H.264 /MJPEG
Скорост на предаване на кадри: Main Stream - 50 Hz: 25 fps (1920x1080, 1280x720), 60 Hz: 30 fps (1920x1080, 1280x720); Sub-Stream - 50 Hz: 25 fps (640x480, 640x360), 60 Hz: 30 fps (640x480, 640x360)
Поддържани мрежови протоколи: TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, NTP, UPnP, SMTP, IGMP, 802.1X, QoS, IPv4, IPv6, UDP, Bonjour, SSL/TLS, PPPoE, SNMP, WebSocket, WebSockets
Мрежов интерфейс: 1 RJ45 10M/100M self-adaptive Ethernet port
Безжична мрежа: -
Power Over Ethernet (PoE): PoE (802.3af, 36 V to 57 V), 0.2 A to 0.12 A, max. 7 W
Входни/Изходни портове: -
Звук: Built-in Microphone
Захранване: 12 VDC, 0.5 A, max. 6.0 W
Слот за карти: Built-in memory card slot, support microSD/microSDHC/microSDXC card, up to 512 GB
Нощно виждане: yes
Външен монтаж: yes

Влагозащита: IP67
Вандалоустойчивост: -
Работна температура: -30 °C to 60 °C
Диапазон на влажността при експлоатация: Humidity 95% or less (non-condensing)
Сигурност: Password protection, complicated password, HTTPS encryption, IP address filter, Security Audit Log, basic and digest authentication for HTTP/HTTPS, TLS 1.1/1.2, WSSE and digest authentication for Open Network Video Interface
Размери (Ш, Д, В), mm: 138.3 x 115.4 mm
Допълнителни функции: Line crossing detection, intrusion detection, region entrance detection, region exiting detection, Supports human and vehicle targets classification

Цена : 256.80 EUR с ДДС

Наличност: Този продукт е бил добавен в нашия каталог на Ср 23 септември, 2026

November 21, 2026, 2:06 a