

МРЕЖОВА ТЕХНИКА > СУИЧОВЕ

Cisco Catalyst 9200L 24-port 8xmGig, 16x1G, 2x25G, PoE+, Network Essentials



Модел : C9200L-24PXG-2Y-E

Cisco Catalyst 9200L 24-port 8xmGig, 16x1G, 2x25G, PoE+, Network Essentials

Суич, тип: Fixed Port

Общ брой портове: 26

Основни портове, тип: 24 ports full PoE+ (8 mGig ports up to 10G, 16 ports up to 1G)

Power Over Ethernet (PoE): IEEE 802.3at PoE+ (up to 30W per port); Available PoE power with single primary power supply (PWR-C5-600WAC): 370W

Uplink портове: 2x 1/10/25G fixed uplinks

Свободни (10GB) слотове: -

Управление: WebUI is an embedded GUI-based device-management tool that provides the ability to provision the device, to simplify device deployment and manageability, and to enhance the user experience

Stackable: Stacking bandwidth: 160 Gbps

Fans: Fixed redundant

Захранване: PWR-C5-600WAC

Routing: Advanced

Памет (Flash, RAM): Flash: 4 GB; DRAM: 4 GB; Packet buffer: 12MB

Капацитет за маршрутизиране/превключване, Gbps: 292 Gbps; Switch capacity with Stacking: 372 Gbps

Пропускателна способност, Mpps: 229.16 Mpps;

Forwarding rate with Stacking: 277 Mpps

MAC адреси: 32 000

VLAN (брой, стандарти): 4; VLAN IDs: 4096;

CISCO-PRIVATE-VLAN-MIB,

CISCO-VLAN-IFTABLE-RELATIONSHIP- MIB, IEEE 802.1Q VLAN

QoS: Superior QoS includes granular wireless bandwidth management and fair sharing, 802.1p Class of Service (CoS) and Differentiated Services Code Point (DSCP) field classification, SRR scheduling, Committed Information Rate (CIR), eight egress queues per port

L2 мрежови стандарти: IEEE 802.1Q, IEEE 802.1D (STP); RSTP, IEEE 802.1w; MSTP, IEEE 802.1s; PVLAN; IEEE 802.3ad (LACP); LLDP; VTP; BPDU Guard

L3 мрежови стандарти: IP Routing (Static, RIP, OSPF, EIGRP), VLAN Routing (SVI, Routing Between VLANs); Multicast Routing (PIM, IGMP); BGP; IPv6; HSRP; VRRP; GLBP; ACLs; PBR

IPv6 functionality: IPv6 routing entries: 2000; Ipv6 routing (using OSPFv3 and EIGRPv6); IPv6 addressing

Сигурност: AES-128 MACsec encryption; Secure Segmentation with Software-Defined Access; Cloud Security - Umbrella Integration

Размери (Ш, Д, В), mm: 445 x 350 x 44 mm

Опция за монтаж: Rackmount

Други: Network Essentials licensing

Цена : 6558.52 EUR с ДДС

Наличност: Този продукт е бил добавен в нашия каталог на Вт 17 февруари, 2026