

МРЕЖОВА ТЕХНИКА > СУИЧОВЕ

D-Link 48-port Gigabit Smart Managed Switch with 4x 10G SFP+ ports



Модел : DGS-1250-52X

D-Link 48-port Gigabit Smart Managed Switch with 4x 10G SFP+ ports

Суич, тип: Fixed Port

Общ брой портове: 52

Основни портове, тип: 48x10/100/1000Base-T

Power Over Ethernet (PoE): No

Uplink портове: 4x10GE SFP

Свободни (10GB) слотове: No

Управление: Web-based GUI, D-Link Network Assistant, Compact CLI, Telnet Server, TFTP Client, Configurable MDI/MDIX, SNMP (Supports v1/v2c/v3), SNMP Trap, BootP/DHCP Client, System Log, ICMP v6, IPv4/v6 Dual Stack, DHCP Auto Configuration, RMONv1

Stackable: No

Fans: Fanless

Захранване: Internal universal power supply: 100 to 240 V AC 50/60 Hz, Maximum Power Consumption: 51.2W

Routing: Layer 3 Lite

Памет (Flash, RAM): Flash Memory: 64 MB, CPU memory: 2G DDR3

Капацитет за маршрутизиране/превключване, Gbps: 176 Gbps

Пропускателна способност, Mpps: 130.95 Mpps

MAC адреси: 32000 MAC address table size

VLAN (брой, стандарти): 802.1Q; VLAN Group - Max. 4094 static VLAN groups; Configurable VID from 1 - 4094; Asymmetric VLAN; Auto Voice VLAN: Max. 10 user-defined OUI, Max. 8 default OUI; Auto Surveillance VLAN

QoS: 802.1p Quality of Service; 8 queues per port; Queue Handling - Strict, Weighted Round Robin (WRR); Bandwidth Control - Port-based (ingress/egress, min granularity 10/100/1000 is 16 Kbps)

L2 мрежови стандарти: IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3z, IEEE 802.3az, IEEE 802.3x, IEEE 802.3ae, IEEE 802.3ad, IEEE 802.1D, IEEE 802.1w, IEEE 802.1s, IEEE 802.1Q, IEEE 802.1p, IEEE 802.1X

L3 мрежови стандарти: Static routing: 124 IPv4 static route entries, 50 IPv6 static route entries

IPv6 functionality: IPv6 Neighbor Discovery (ND); IPv6 address: Source/destination IP address mask, DSCP mask, Protocol type mask, TCP/UDP port number mask, IPv6 traffic class mask; IPv6 Inspection (Max. 63 entries); IPv6 RADIUS

server

Сигурност: Broadcast/Multicast/Unicast Storm Control, D-Link Safeguard Engine, Traffic segmentation, SSH v2, TLS v.1.2, DoS attack prevention, 802.1X, Port Security - Supports up to 64 MAC addresses per port, ARP Spoofing Prevention, DHCP, IP-MAC-Port Binding

Размери (Ш, Д, В), mm: 440 x 210 x 44 mm

Опция за монтаж: Rackmount

Други: RJ-45 console Port for CLI management

Цена : 743.65 EUR с ДДС

Наличност: Този продукт е бил добавен в нашия каталог на Чт 26 февруари, 2026