МРЕЖОВА ТЕХНИКА > СУИЧОВЕ

D-Link 24-port Gigabit PoE Smart Managed Switch with 4x 10G SFP+ ports, 370Watts



Модел : DGS-1250-28XMP
D-Link 24-port Gigabit PoE Smart Managed Switch with 4x 10G SFP+ ports, 370Watts
Суич, тип: Fixed Port
Общ брой портове: 28
Основни портове, тип: 24x10/100/1000Base-T
Power Over Ethernet (PoE): IEEE 802.3af/at PoE Standard; 24 PoE Capable Ports; PoE Power Budget: 370 W
Uplink портове: 4x10GE SFP
Свободни (10GB) слотове: No
Управление: Web-based GUI, D-Link Network Assistant, Compact CLI, Telnet Server, TFTP Client, Configurable MDI/MDIX, SNMP (Supports v1/v2c/v3), SNMP Trap, BootP/DHCP Client, System Log, ICMP v6, IPv4/v6 Dual Stack, DHCP Auto Configuration, RMONv1
Stackable: No
Fans: Fanless
Захранване: Internal universal power supply: 100 to 240 V AC 50/60 Hz, Maximum Power Consumption: 431.5 W (PoE On), 39.1 W (PoE Off)
Routing: Layer 3 Lite
Памет (Flash, RAM): Flash Memory: 64 MB, CPU memory: 2G DDR3
Капацитет за маршрутизиране/превключване, Gbps: 128 Gbps
Пропускателна способност, Mpps: 95.24 Mpps
MAC адреси: 16000 MAC address table size
VLAN (брой, стандарти): 802.1Q; VLAN Group - Max. 4094 static VLAN groups; Configurable VID from 1 - 4094; Asymmetric VLAN; Auto Voice VLAN: Max. 10 user-defined OUI, Max. 8 default OUI; Auto Surveillance VLAN
QoS: 802.1p Quality of Service; 8 queues per port; Queue Handling - Strict, Weighted Round Robin (WRR); Bandwidth Control - Port-based (ingress/egress, min granularity 10/100/1000 is 16 Kbps)
L2 мрежови стандарти: IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3z, IEEE 802.3az, IEEE 802.3x, IEEE 802.3ae, IEEE 802.3ad, IEEE 802.1D, IEEE 802.1w, IEEE 802.1s, IEEE 802.1Q, IEEE 802.1p, IEEE 802.1X, IEEE 802.3af, IEEE 802.3at
L3 мрежови стандарти: Static routing: 124 IPv4 static route entries, 50 IPv6 static route entries

November 22, 2026, 2:3

IPv6 functionality: IPv6 Neighbor Discovery (ND); IPv6 address: Source/destination IP address mask, DSCP mask, Protocol type mask, TCP/UDP port number mask, IPv6 traffic class mask; IPv6 Inspection (Max. 63 entries); IPv6 RADIUS server

Сигурност: Broadcast/Multicast/Unicast Storm Control, D-Link Safeguard Engine, Traffic segmentation, SSH v2, TLS v.1.2, DoS attack prevention, 802.1X, Port Security - Supports up to 64 MAC addresses per port, ARP Spoofing Prevention, DHCP, IP-MAC-Port Binding

Размери (Ш, Д, В), mm: 440 x 250 x 44 mm

Опция за монтаж: Rackmount

Други: RJ-45 console Port for CLI management

Цена : 654.22 EUR с ДДС

Наличност: Този продукт е бил добавен в нашия каталог на Чт 26 февруари, 2026

November 22, 2026 9:39 p.