МРЕЖОВА ТЕХНИКА > СУИЧОВЕ

D-Link 52-Port Gigabit Stackable POE Smart Managed Switch including 4 10G SFP+



Модел : DGS-1510-52XMP
D-Link 52-Port Gigabit Stackable POE Smart Managed Switch including 4 10G SFP+
Суич, тип: Fixed Port
Общ брой портове: 52
Основни портове, тип: 48x10/100/1000Base-T
Power Over Ethernet (PoE): IEEE 802.3af and IEEE 802.3at PoE Standard; PoE Capable Ports (Ports 1 to 48: Up to 30 W); PoE Power Budget: Max. 370 W (740 W with DPS-700 RPS redundant power supply)
Uplink портове: 4x10GE SFP
Свободни (10GB) слотове: No
Управление: CLI, Telnet Server, TFTP Client, IPv6 Neighbor Discovery, Configurable MDI/MDIX, SNMP (Supports v1, v2c, v3), SNMP Trap, System Log, DHCP Client, D-Link Network Assistant support, SNTP, ICMPv6, IPv4/v6 Dual Stack, DHCP Auto Configuration, RMON v1
Stackable: Virtual Stacking Support: D-Link Single IP Management, Up to 32 devices per virtual stack, Up to 20G stacking bandwidth; Physical Stacking: Supports Duplex Chain/Ring topology, Up to 40G stacking bandwidth full duplex, Up to 6 units per stack
Fans: 4 x smart fans
Захранване: Internal Universal Power Supply: 100 - 240 VAC, 50/60 Hz
Routing: Layer 3 Lite
Памет (Flash, RAM): -
Капацитет за маршрутизиране/превключване, Gbps: 176 Gbps
Пропускателна способност, Mpps: 130.95 Mpps
MAC адреси: 16000 MAC address table size
VLAN (брой, стандарти): 802.1Q Tagged VLAN, 4K VLAN Groups, Configurable VID: 0~4094, GVRP, Asymmetric VLAN, Auto Voice VLAN, Auto Surveillance VLAN, MAC-based VLAN, Protocol-based VLAN
QoS: 802.1p Quality of Service, Queue Handling (Strict Priority Queue(SPQ), Weighted Round Robin(WRR), Deficit Round Robin(DRR), SPQ+WRR), 8 queues per port, Bandwidth Control-Port-based (Ingress/Egress, min. granularity for 10/100/1000 BASE-T ports is 64Kb/s)
L2 мрежови стандарти: IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, 802.3ae, IEEE 802.3af, IEEE 802.3at, IEEE 802.3x,

November 22, 2026, 2:3

Spanning Tree Protocol: IEEE 802.1D STP, IEEE 802.1w RSTP, IEEE 802.1s MSTP; IEEE 802.3ad Link Aggregation, IEEE 802.3az Energy Efficient Ethernet

L3 мрежови стандарти: Default Routing, Static Routing: 64 IPv4 Static Route Entries, 32 IPv6 Static Route Entries

IPv6 functionality: IPv6 ready and supports various IPv6 functions such as MLD Snooping, IPv6 security features, and IPv6 Quality of Service (QoS), ensuring seamless integration with next generation networks. IPv4/v6 dual stack functionality

Сигурност: Port Security, Broadcast/Multicast/Unicast Storm Control, Dynamic ARP Inspection, D-Link Safeguard Engine, DHCP Server Screening, ARP Spoofing Prevention, SSH, SSL, Traffic Segmentation, IP-MAC-Port Binding, DoS Attack Prevention, ACLs

Размери (Ш, Д, В), mm: 440 x 308 x 44 mm

Опция за монтаж: Rackmount

Цена : 1829.70 EUR с ДДС

Наличност: Този продукт е бил добавен в нашия каталог на Чт 26 февруари, 2026

November 22, 2026, 9:34 p.