МРЕЖОВА ТЕХНИКА > СУИЧОВЕ

D-Link 20-port GE PoE 370W Layer 3 Stackable Managed Gigabit Switch including 4-port Combo 4-port Combo



Модел : DGS-3630-28PC/SI
D-Link 20-port GE PoE 370W Layer 3 Stackable Managed Gigabit Switch including 4-port Combo 4-port Combo
Суич, тип: Fixed Port
Общ брой портове: 28
Основни портове, тип: 20x10/100/1000Base-T
Power Over Ethernet (PoE): IEEE 802.3af/at PoE Standards; PoE Power Budget: 370 W (740 W with DPS-700 RPS redundant power supply)
Uplink портове: 4 dual personality, 4x10GE SFP
Свободни (10GB) слотове: No
Управление: Web-based GUI, Command Line Interface (CLI), Telnet Server, Telnet Client, SNMP v1/v2c/v3, SNMP Trap, TFTP, FTP, RCP, SMTP, RMONv1 (Supports 1,2,3,9 groups), RMONv2 (Supports ProbeConfig group), D-Link Discover Protocol (DDP), sFlow, Debug Command
Stackable: Physical Stacking: Up to 80 Gbps stacking bandwidth, Up to 9 switches in a stack, Ring/chain topology support; Virtual Stacking/Clustering of up to 32 units: Supports D-Link Single IP Management, Up to 20 Gbps stacking bandwidth
Fans: 4 x smart fans
Захранване: Power Input: 100 to 240 VAC 50/60 Hz, Optional Redundant Power Supply: DPS-700
Routing: Layer 3 RIP
Памет (Flash, RAM): -
Капацитет за маршрутизиране/превключване, Gbps: 128 Gbps
Пропускателна способност, Mpps: 95.24 Mpps
MAC адреси: 68000 MAC address table size
VLAN (брой, стандарти): VLAN Group: Max. 4K VLAN groups, Max. 4094 VIDs; Multicast VLAN (ISM VLAN for IPv4/IPv6); Voice VLAN; Auto Surveillance VLAN; VLAN Trunking; GVRP: Up to 4K dynamic VLANs; Asymmetric VLAN; 802.1Q; 802.1v Protocol-based VLAN; Double VLAN; Private VLAN
QoS: 802.1p, 8 queues per port, Queue Handling (Strict Priority (SP), Weighted Round Robin (WRR), Strict + WRR, Weighted Deficit Round Robin (WDRR)), Congestion Control, 802.1Qbb Priority-based Flow Control (PFC) for 10 GbE port, Bandwidth Control, Policy Map
L2 мрежови стандарти: IEEE 802.3ah, IEEE 802.1ag, IEEE

November 22, 2026, 2:4

802.3x, IEEE 802.1D, IEEE 802.1w, IEEE 802.1s, IEEE 802.1X, IEEE 802.1Q, IEEE 802.1Qbb, IEEE 802.1p, IEEE 802.1v, IEEE 802.1AX, IEEE 802.1ak, IEEE 802.3af, IEEE 802.3at

L3 мрежови стандарти: Static Route: Max. 512 IPv4 entries, Max. 256 IPv6 entries; IPv4/IPv6 Default Route; BFD (Bidirectional Forwarding Detection) - IPv4/v6 Static Route, RIP, VRRP; RIPv1/v2/ng

IPv6 functionality: IPv6 Tunnelling: Static, ISATAP, GRE, 6to4; IPv6 Traffic Class; IPv6 Flow Label

Сигурност: Port Security, Broadcast/Multicast/Unicast Storm Control, D-Link Safeguard Engine, DHCP Server Screening, Dynamic ARP Inspection, IP Source Guard, DHCP Snooping, IPv6 Snooping, Dynamic ARP Inspection (DAI), SSL, SSH, BPDU Attack Prevention

Размери (Ш, Д, В), mm: 441 x 380 x 44 mm

Опция за монтаж: Rackmount

Други: RJ45 and Mini USB console ports for out-of-band CLI management, 10/100/1000BASE-T RJ-45 Ethernet for out-of-band IP management, 1 RJ-45 port Alarm port, 1 USB 2.0 Type A port, Stacking cable and USB flash card not included

Цена : 3514.63 EUR с ДДС

Наличност: Този продукт е бил добавен в нашия каталог на Чт 26 февруари, 2026

November 22, 2025