МРЕЖОВА ТЕХНИКА > СУИЧОВЕ

D-Link 10G Layer 3 Stackable Managed Switches



Модел : DXS-3410-32SY
D-Link 10G Layer 3 Stackable Managed Switches
Суич, тип: Fixed Port
Общ брой портове: 32
Основни портове, тип: 28x10GE SFP
Power Over Ethernet (PoE): No
Uplink портове: 4x10G/25G SFP28
Свободни (10GB) слотове: No
Управление: Web-based GUI, CLI, Telnet Server/Client, TFTP Client, DNS Client, SNMP (Supports v1/v2c/v3), SNMP Traps, sFlow, Multiple images/ Multiple Configurations, RMON v1/v2, LLDP/LLDP-MED, Flash File System, DDP, NTPv3/v4, Password recovery/encryption, SMTP
Stackable: 4 Stacking Ports; Physical stacking - Up to 9 units per stack, Up to 200 Gbps stacking bandwidth, Ring/chain topology support; Virtual stacking - D-Link Single IP Management (SIM), Up to 32 units per virtual stack
Fans: 3x Smart fans
Захранване: Optional Redundant Power Supply: DPS-500A, DPS-500DC
Routing: Layer 3 Advanced
Памет (Flash, RAM): -
Капацитет за маршрутизиране/превключване, Gbps: 760 Gbps
Пропускателна способност, Mpps: 565.44 Mpps
MAC адреси: 32000 MAC address table size
VLAN (брой, стандарти): 802.1Q, 802.1v, Double VLAN (Q-in-Q), Port/MAC-based VLAN, Auto Surveillance/Voice VLAN, VLAN translation, Multicast/Asymmetric/Private/Super VLAN, VLAN Trunking, GVRP - Max. 4K dynamic VLAN groups, VLAN Group: Max. 4K VLAN groups, Max. 1~4094 VIDs
QoS: 802.1p Quality of Service (QoS), 8 queues per port, Queue handling (Strict, Weighted Round Robin (WRR), Strict + WRR, Weighted Deficit Round Robin (WDRR)), Bandwidth Control, Congestion Control, Policy Map, Three Color Marker
L2 мрежови стандарти: IEEE 802.1D, IEEE 802.1w, IEEE 802.1s, IEEE 802.3x, IEEE 802.1X, IEEE 802.1Q, IEEE 802.1v, IEEE 802.1AX, IEEE 802.1p, IEEE 802.1Qbb, IEEE 802.3ah, IEEE 802.1ag, IEEE 802.3ad
L3 мрежови стандарти: Static Route, RIPv1/v2/ng, OSPFv2/v3
IPv6 functionality: IPv6 traffic class, IPv6 flow label, IPv6

November 22, 2024, 2:34

Snooping, IPv6 Route Advertisement (RA) Guard, IPv6 ND Inspection
Сигурност: Port Security, Broadcast/Multicast/Unicast Storm Control, D-Link Safeguard Engine, DHCP Server Screening, Dynamic ARP Inspection, IP Source Guard, DHCP Snooping, DHCPv6 Guard, BPDU Attack Protection, DOS Attack Prevention, SSH, SSL, Traffic Segmentation
Размери (Ш, Д, В), mm: 441 x 250 x 44 mm
Опция за монтаж: Rackmount
Други: Console Port: RJ-45 port for out-of-band CLI management, Management Port: 10/100/1000BASE-T RJ-45 port for out-of-band IP management, 1x USB 2.0 Type A port

Цена : 2483.94 EUR с ДДС

Наличност: Този продукт е бил добавен в нашия каталог на Чт 26 февруари, 2026

November 21, 2026, 8:34 p.