

МРЕЖОВА ТЕХНИКА > СУИЧОВЕ

D-Link 10G Layer 3 Stackable Managed Switches



Модел : DXS-3410-32XY

D-Link 10G Layer 3 Stackable Managed Switches

Суич, тип: Fixed Port

Общ брой портове: 32

Основни портове, тип: 24x10GBase-T

Power Over Ethernet (PoE): No

Uplink портове: 4x10GE SFP, 4x10G/25G SFP28

Свободни (10GB) слотове: No

Управление: Web-based GUI, CLI, Telnet Server/Client, TFTP Client, DNS Client, SNMP (Supports v1/v2c/v3), SNMP Traps, sFlow, Multiple images/ Multiple Configurations, RMON v1/v2, LLDP/LLDP-MED, Flash File System, DDP, NTPv3/v4, Password recovery/encryption, SMTP

Stackable: 4 Stacking Ports; Physical stacking - Up to 9 units per stack, Up to 200 Gbps stacking bandwidth, Ring/chain topology support; Virtual stacking - D-Link Single IP Management (SIM), Up to 32 units per virtual stack

Fans: 3x Smart fans

Захранване: Optional Redundant Power Supply: DPS-500A, DPS-500DC

Routing: Layer 3 Advanced

Памет (Flash, RAM): -

Капацитет за маршрутизиране/превключване, Gbps: 760 Gbps

Пропускателна способност, Mpps: 565.44 Mpps

MAC адреси: 32000 MAC address table size

VLAN (брой, стандарти): 802.1Q, 802.1v, Double VLAN (Q-in-Q), Port/MAC-based VLAN, Auto Surveillance/Voice VLAN, VLAN translation, Multicast/Asymmetric/Private/Super VLAN, VLAN Trunking, GVRP - Max. 4K dynamic VLAN groups, VLAN Group: Max. 4K VLAN groups, Max. 1~4094 VIDs

QoS: 802.1p Quality of Service (QoS), 8 queues per port, Queue handling (Strict, Weighted Round Robin (WRR), Strict + WRR, Weighted Deficit Round Robin (WDRR)), Bandwidth Control, Congestion Control, Policy Map, Three Color Marker

L2 мрежови стандарти: IEEE 802.1D, IEEE 802.1w, IEEE 802.1s, IEEE 802.3x, IEEE 802.1X, IEEE 802.1Q, IEEE 802.1v, IEEE 802.1AX, IEEE 802.1p, IEEE 802.1Qbb, IEEE 802.3ah, IEEE 802.1ag, IEEE 802.3ad

L3 мрежови стандарти: Static Route, RIPv1/v2/ng, OSPFv2/v3

IPv6 functionality: IPv6 traffic class, IPv6 flow label, IPv6

Snooping, IPv6 Route Advertisement (RA) Guard, IPv6 ND Inspection

Сигурност: Port Security, Broadcast/Multicast/Unicast Storm Control, D-Link Safeguard Engine, DHCP Server Screening, Dynamic ARP Inspection, IP Source Guard, DHCP Snooping, DHCPv6 Guard, BPDU Attack Protection, DOS Attack Prevention, SSH, SSL, Traffic Segmentation

Размери (Ш, Д, В), mm: 441 x 250 x 44 mm

Опция за монтаж: Rackmount

Други: Console Port: RJ-45 port for out-of-band CLI management, Management Port: 10/100/1000BASE-T RJ-45 port for out-of-band IP management, 1x USB 2.0 Type A port

Цена : 3925.90 EUR с ДДС

Наличност: Този продукт е бил добавен в нашия каталог на Чт 26 февруари, 2026