

МРЕЖОВА ТЕХНИКА > СУИЧОВЕ

D-Link 30-Port Layer 3 Stackable Multi-Gigabit Managed PoE Switch



Модел : DMS-3130-30PS

D-Link 30-Port Layer 3 Stackable Multi-Gigabit Managed PoE Switch

Суич, тип: Fixed Port

Общ брой портове: 30

Основни портове, тип: 16x10/100/1000/2500Base-T

Power Over Ethernet (PoE): IEEE 802.3af/at/bt PoE

Standard, PoE Power Budget: 740 W, 960 W (dual PSU)

Uplink портове: 8x100/1000/2.5G/5GBase-T, 2x10GBase-T, 4x10G/25G SFP28

Свободни (10GB) слотове: No

Управление: Web-based GUI, Command Line Interface (CLI), SNMP, RMON v1/v2, LLDP/LLDP-MED, BootP/DHCP Client, DHCP, Flash File System, D-Link Discover Protocol (DDP), Debug command, NTPv3/v4, Command Logging, Ping/Traceroute for IPv4/IPv6, Password recovery/encryption

Stackable: Physical stacking: Up to 9 units per stack, Up to 200 Gbps stacking bandwidth, Ring/chain topology support; Virtual stacking: D-Link Single IP Management (SIM), Up to 32 units per virtual stack; 4 Stacking Ports

Fans: 2x Smart fan

Захранване: Power Input: 100 to 240 V AC 50/60 Hz, Hot Swappable Power Supply: Up to 2 (1 included), Max Power Consumption: 1211.5 W (PoE On) / 88.9 W (PoE Off), Standby: 58.3 W

Routing: Layer 3 Advanced

Памет (Flash, RAM): Packet Buffer Memory: 4 MB

Капацитет за маршрутизиране/превключване, Gbps: 400 Gbps

Пропускателна способност, Mpps: 298 Mpps

MAC адреси: 32000 MAC address table size

VLAN (брой, стандарти): VLAN Group: Max. 4K VLAN groups, Max. 1~4094 VIDs; GVRP (Max. 4K dynamic VLAN groups); Double VLAN (Q-in-Q); 802.1Q; Port-based VLAN; 802.1v Protocol-based VLAN; MAC-based VLAN; VLAN translation; Multicast/Asymmetric/Private VLAN; VLAN Trunking; Super VLAN

QoS: 802.1p Quality of Service; 8 queues per port; Queue Handling - Strict, Weighted Round Robin (WRR), Strict + WRR, Weighted Deficit Round Robin (WDRR); Policy Map - Remark 802.1p priority, Remark IP precedence/DSCP; Congestion Control - WRED

L2 мрежови стандарти: IEEE 802.3af, IEEE 802.3at, IEEE

802.3bt, IEEE 802.1p, IEEE 802.1X, IEEE 802.3ah, IEEE 802.1ag, IEEE 802.3ad, IEEE 802.3x, IEEE 802.1AX, IEEE 802.1D, IEEE 802.1w, IEEE 802.1s, IEEE 802.1Q, IEEE 802.1v

L3 мрежови стандарти: Static Route, RIPv1/v2/ng, OSPFv2/v3

IPv6 functionality: IPv6 traffic class, IPv6 Flow Label, IPv6 Snooping, IPv6 Route Advertisement (RA) Guard, IPv6 ND Inspection

Сигурност: Broadcast/Multicast/Unicast Storm Control, D-Link Safeguard Engine, Port Security - Supports up to 64 MAC addresses per port, Dynamic ARP Inspection (DAI), DHCPv6 Guard, IP Source Guard, Duplicate Address Detection (DAD), Traffic Segmentation, SSL, SSH

Размери (Ш, Д, В), mm: 440 x 470 x 44 mm

Опция за монтаж: Rackmount

Други: 10/100/1000BASE-T RJ-45 port for out-of-band CLI management, 10/100/1000BASE-T RJ-45 port for out-of-band IP management, 1x USB 2.0 Type A port

Цена : 4185.94 EUR с ДДС

Наличност: Този продукт е бил добавен в нашия каталог на Чт 26 февруари, 2026