

МРЕЖОВА ТЕХНИКА > СУИЧОВЕ

D-Link 24x10/100/1000Base-T PoE ports (370W budget) Layer 3 Stackable Managed Gigabit Switch with 2x10GBASE-T ports and 4xSFP+ ports



Модел : DGS-3130-30PS

D-Link 24x10/100/1000Base-T PoE ports (370W budget) Layer 3 Stackable Managed Gigabit Switch with 2x10GBASE-T ports and 4xSFP+ ports

Суич, тип: Fixed Port

Общ брой портове: 30

Основни портове, тип: 24x10/100/1000Base-T

Power Over Ethernet (PoE): IEEE 802.3af, IEEE 802.3at PoE Standards; PoE Power Budget: 370 W, 740 W (with DPS-700 RPS)

Uplink портове: 4x10GE SFP, 2x10GBase-T

Свободни (10GB) слотове: No

Управление: Web-based GUI, Command Line Interface (CLI), SNMP, RMON v1/v2, LLDP/LLDP-MED, BootP/DHCP Client, DHCP, Flash File System, D-Link Discover Protocol (DDP), Debug command, NTPv3/v4, Command Logging, Ping/Traceroute for IPv4/IPv6, Password recovery/encryption

Stackable: 4 Stacking Ports; Physical stacking: Stacking Lite, Up to 80 Gbps stacking bandwidth, Ring/chain topology support; Virtual stacking: D-Link Single IP Management (SIM), Up to 32 units per virtual stack

Fans: 3x Smart fans

Захранване: Power Input: 100 to 240 V AC 50/60 Hz; Max Power Consumption: Max.: 454.55 W (PoE On), 38.74 W (PoE Off), Standby - 19.63 W; Optional Redundant Power Supply: DPS-700

Routing: Layer 3 Advanced

Памет (Flash, RAM): Packet Buffer Memory: 2 MB

Капацитет за маршрутизиране/превключване, Gbps: 168 Gbps

Пропускателна способност, Mpps: 125 Mpps

MAC адреси: 16000 MAC address table size

VLAN (брой, стандарти): VLAN Group: Max. 4K VLAN groups, Max. 1~4094 VIDs; GVRP (Max. 4K dynamic VLAN groups); Double VLAN (Q-in-Q); 802.1Q; Port-based VLAN; 802.1v Protocol-based VLAN; MAC-based VLAN; VLAN translation; Multicast/Asymmetric/Private VLAN; VLAN Trunking; Super VLAN

QoS: 802.1p Quality of Service; 8 queues per port; Queue Handling - Strict, Weighted Round Robin (WRR), Strict + WRR, Weighted Deficit Round Robin (WDRR); Policy Map -

Remark 802.1p priority, Remark IP precedence/DSCP, Time based QoS; Congestion Control - WRED

L2 мрежови стандарти: IEEE 802.1p, IEEE 802.1X, IEEE 802.3ah, IEEE 802.1ag, IEEE 802.3ad, IEEE 802.3x, IEEE 802.1AX, IEEE 802.1D, IEEE 802.1w, IEEE 802.1s, IEEE 802.1Q, IEEE 802.1v, IEEE 802.3af, IEEE 802.3at

L3 мрежови стандарти: Static Route, RIPv1/v2/ng, OSPFv2/v3

IPv6 functionality: IPv6 traffic class, IPv6 Flow Label, IPv6 Snooping, IPv6 Route Advertisement (RA) Guard, IPv6 ND Inspection

Сигурност: Broadcast/Multicast/Unicast Storm Control, D-Link Safeguard Engine, Port Security - Supports up to 64 MAC addresses per port, Dynamic ARP Inspection (DAI), DHCPv6 Guard, IP Source Guard, Duplicate Address Detection (DAD), Traffic Segmentation, SSL, SSH

Размери (Ш, Д, В), mm: 440 x 430 x 44 mm

Опция за монтаж: Rackmount

Други: 10/100/1000BASE-T RJ-45 port for out-of-band CLI management, 10/100/1000BASE-T RJ-45 port for out-of-band IP management, 1x USB 2.0 Type A port

Цена : 1506.98 EUR с ДДС

Наличност: Този продукт е бил добавен в нашия каталог на Чт 26 февруари, 2026