

МРЕЖОВА ТЕХНИКА > СУИЧОВЕ

D-Link 24 SFP ports Layer 3 Stackable Managed Gigabit Switch with 2x10GBASE-T ports and 4xSFP+ ports



Модел : DGS-3130-30S

D-Link 24 SFP ports Layer 3 Stackable Managed Gigabit Switch with 2x10GBASE-T ports and 4xSFP+ ports

Суич, тип: Fixed Port

Общ брой портове: 30

Основни портове, тип: 24xSFP

Power Over Ethernet (PoE): No

Uplink портове: 4x10GE SFP, 2x10GBase-T

Свободни (10GB) слотове: No

Управление: Web-based GUI, Command Line Interface (CLI), SNMP, RMON v1/v2, LLDP/LLDP-MED, BootP/DHCP Client, DHCP, Flash File System, D-Link Discover Protocol (DDP), Debug command, NTPv3/v4, Command Logging, Ping/Traceroute for IPv4/IPv6, Password recovery/encryption

Stackable: 4 Stacking Ports; Physical stacking: Stacking Lite, Up to 80 Gbps stacking bandwidth, Ring/chain topology support; Virtual stacking: D-Link Single IP Management (SIM), Up to 32 units per virtual stack

Fans: 3x Smart fans

Захранване: Power Input: 100 to 240 V AC 50/60 Hz; Max Power Consumption: 65.01 W, Standby - 22.77 W; Optional Redundant Power Supply: DPS-500A

Routing: Layer 3 Advanced

Памет (Flash, RAM): Packet Buffer Memory: 2 MB

Капацитет за маршрутизиране/превключване, Gbps: 168 Gbps

Пропускателна способност, Mpps: 125 Mpps

MAC адреси: 16000 MAC address table size

VLAN (брой, стандарти): VLAN Group: Max. 4K VLAN groups, Max. 1~4094 VIDs; GVRP (Max. 4K dynamic VLAN groups); Double VLAN (Q-in-Q); 802.1Q; Port-based VLAN; 802.1v Protocol-based VLAN; MAC-based VLAN; VLAN translation; Multicast/Asymmetric/Private VLAN; VLAN Trunking; Super VLAN

QoS: 802.1p Quality of Service; 8 queues per port; Queue Handling - Strict, Weighted Round Robin (WRR), Strict + WRR, Weighted Deficit Round Robin (WDRR); Policy Map - Remark 802.1p priority, Remark IP precedence/DSCP, Time based QoS; Congestion Control - WRED

L2 мрежови стандарти: IEEE 802.1p, IEEE 802.1X, IEEE 802.3ah, IEEE 802.1ag, IEEE 802.3ad, IEEE 802.3x, IEEE 802.1AX, IEEE 802.1D, IEEE 802.1w, IEEE 802.1s, IEEE

802.1Q, IEEE 802.1v

L3 мрежови стандарти: Static Route, RIPv1/v2/ng, OSPFv2/v3

IPv6 functionality: IPv6 traffic class, IPv6 Flow Label, IPv6 Snooping, IPv6 Route Advertisement (RA) Guard, IPv6 ND Inspection

Сигурност: Broadcast/Multicast/Unicast Storm Control, D-Link Safeguard Engine, Port Security - Supports up to 64 MAC addresses per port, Dynamic ARP Inspection (DAI), DHCPv6 Guard, IP Source Guard, Duplicate Address Detection (DAD), Traffic Segmentation, SSL, SSH

Размери (Ш, Д, В), mm: 440 x 250 x 44 mm

Опция за монтаж: Rackmount

Други: 10/100/1000BASE-T RJ-45 port for out-of-band CLI management, 10/100/1000BASE-T RJ-45 port for out-of-band IP management, 1x USB 2.0 Type A port

Цена : 1203.14 EUR с ДДС

Наличност: Този продукт е бил добавен в нашия каталог на Чт 26 февруари, 2026