*МРЕЖОВА ТЕХНИКА > СУИЧОВЕ*

# D-Link 48x10/100/1000BASE-T PoE ports (370W budget) Layer 3 Stackable Managed Gigabit Switch with 2x10GBASE-T ports and 4xSFP+ ports



Модел : DGS-3130-54PS
D-Link 48x10/100/1000BASE-T PoE ports (370W budget) Layer 3 Stackable Managed Gigabit Switch with 2x10GBASE-T ports and 4xSFP+ ports
Суич, тип: Fixed Port
Общ брой портове: 54
Основни портове, тип: 48x10/100/1000Base-T
Power Over Ethernet (PoE): IEEE 802.3af, IEEE 802.3at PoE Standards; PoE Power Budget: 370 W, 740 W (with DPS-700 RPS)
Uplink портове: 4x10GE SFP, 2x10GBase-T
Свободни (10GB) слотове: No
Управление: Web-based GUI, Command Line Interface (CLI), SNMP, RMON v1/v2, LLDP/LLDP-MED, BootP/DHCP Client, DHCP, Flash File System, D-Link Discover Protocol (DDP), Debug command, NTPv3/v4, Command Logging, Ping/Traceroute for IPv4/IPv6, Password recovery/encryption
Stackable: 4 Stacking Ports; Physical stacking: Stacking Lite, Up to 80 Gbps stacking bandwidth, Ring/chain topology support; Virtual stacking: D-Link Single IP Management (SIM), Up to 32 units per virtual stack
Fans: 4x Smart fans
Захранване: Power Input: 100 to 240 V AC 50/60 Hz; Max Power Consumption: Max.: 474.51 W (PoE On), 62.25 W (PoE Off), Standby - 36.48 W; Optional Redundant Power Supply: DPS-700
Routing: Layer 3 Advanced
Памет (Flash, RAM): Packet Buffer Memory: 4 MB
Капацитет за маршрутизиране/превключване, Gbps: 216 Gbps
Пропускателна способност, Mpps: 161 Mpps
MAC адреси: 16000 MAC address table size
VLAN (брой, стандарти): VLAN Group: Max. 4K VLAN groups, Max. 1~4094 VIDs; GVRP (Max. 4K dynamic VLAN groups); Double VLAN (Q-in-Q); 802.1Q; Port-based VLAN; 802.1v Protocol-based VLAN; MAC-based VLAN; VLAN translation; Multicast/Asymmetric/Private VLAN; VLAN Trunking;Super VLAN
QoS: 802.1p Quality of Service; 8 queues per port; Queue Handling - Strict, Weighted Round Robin (WRR), Strict + WRR, Weighted Deficit Round Robin (WDRR); Policy Map -

November 22, 2020, 2:

Remark 802.1p priority, Remark IP precedence/DSCP, Time based QoS; Congestion Control - WRED
L2 мрежови стандарти: IEEE 802.1p, IEEE 802.1X, IEEE 802.3ah, IEEE 802.1ag, IEEE 802.3ad, IEEE 802.3x, IEEE 802.1AX, IEEE 802.1D, IEEE 802.1w, IEEE 802.1s, IEEE 802.1Q, IEEE 802.1v, IEEE 802.3af, IEEE 802.3at
L3 мрежови стандарти: Static Route, RIPv1/v2/ng, OSPFv2/v3
IPv6 functionality: IPv6 traffic class, IPv6 Flow Label, IPv6 Snooping, IPv6 Route Advertisement (RA) Guard, IPv6 ND Inspection
Сигурност: Broadcast/Multicast/Unicast Storm Control, D-Link Safeguard Engine, Port Security - Supports up to 64 MAC addresses per port, Dynamic ARP Inspection (DAI), DHCPv6 Guard, IP Source Guard, Duplicate Address Detection (DAD), Traffic Segmentation, SSL, SSH
Размери (Ш, Д, В), mm: 440 x 430 x 44 mm
Опция за монтаж: Rackmount
Други: 10/100/1000BASE-T RJ-45 port for out-of-band CLI management, 10/100/1000BASE-T RJ-45 port for out-of-band IP management, 1x USB 2.0 Type A port

## Цена : 2416.30 EUR с ДДС

*Наличност: Този продукт е бил добавен в нашия каталог на  Чт 26 февруари, 2026*

November 22, 2026 2:54 p.