

КОМПЮТЪРНИ КОМПОНЕНТИ > Дънни Платки

ASUS TUF GAMING B850-PLUS WIFI



Модел : ASUS TUF GAMING B850-PLUS WIFI

ASUS TUF GAMING B850-PLUS WIFI

USB: Rear USB (Total 10 ports); 1 x USB 20Gbps port (1 x USB Type-C®); 3 x USB 10Gbps ports (3 x Type-A); 4 x USB 5Gbps ports (4 x Type-A); 2 x USB 2.0 ports (2 x Type-A); Front USB (Total 7 ports); 1 x USB 10Gbps connector (supports USB Type-C®); 1 x USB 5Gbps header supports 2 additional USB 5Gbps ports; 2 x USB 2.0 headers support 4 additional USB 2.0 ports

Manufacturer: ASUS

Wireless: Wi-Fi 7 2x2 Wi-Fi 7 (802.11be); Supports 2.4/5/6GHz frequency band**; Supports Wi-Fi 7 160MHz bandwidth, up to 2.9Gbps transfer rate

Memory type: 4 x DIMM slots, max. 256GB, DDR5; Supports up to 8000+MT/s (OC) with Ryzen™ 9000 & 8000 & 7000 Series Processors, ECC and Non-ECC Un-buffered DIMM; Dual channel memory architecture; Supports AMD Extended Profiles for Overclocking (EXPO™); ASUS Enhanced Memory Profile (AEMP)

Features: ASUS TUF PROTECTION; - DIGI+ VRM (- Digital power design with DrMOS); - ESD Guards; - TUF LANGuard; - Overvoltage protection; - SafeSlot; - Stainless-steel back I/O; ASUS Q-Design; - M.2 Q-Latch; - PCIe Slot Q-Release; - Q-Antenna; - Q-Dashboard; - Q-DIMM; - Q-LED (CPU [red], DRAM [yellow], VGA [white], Boot Device [yellow green]); - Q-Slot; ASUS Thermal Solution; - M.2 heatsink; - VRM heatsink design; ASUS EZ DIY; - BIOS FlashBack™ button; - BIOS FlashBack™ LED; - ProCool; - Pre-mounted I/O shield; - SafeDIMM; Aura Sync; - Addressable Gen 2 headers
CPU's supported: AMD Socket AM5 for AMD Ryzen™ 9000 & 8000 & 7000 Series Desktop Processors

Chipset: AMD B850 Chipset

Bluetooth: Bluetooth® v5.4

Graphics: 1 x DisplayPort; 1 x HDMI™ port

Expansion Slots: AMD Ryzen™ 9000 & 7000 Series Desktop Processors; 1 x PCIe 5.0 x16 slot (supports x16 mode); AMD Ryzen™ 8000 Series Desktop Processors; 1 x PCIe 4.0 x16 slot (supports x8/x4 mode); AMD B850 Chipset; 1 x PCIe 4.0 x16 slot (supports x4 mode)***; 2 x PCIe 4.0 x1 slots

Storage: Total supports 3 x M.2 slots and 4 x SATA 6Gb/s ports; AMD Ryzen™ 9000 & 7000 Series Desktop Processors; M.2_1 slot (Key M), type 2280 (supports PCIe 5.0 x4 mode); M.2_2 slot (Key M), type 2242/2260/2280/22110

(supports PCIe 4.0 x4 mode);AMD Ryzen™ 8000 Series Desktop Processors;M.2_1 slot (Key M), type 2280 (supports PCIe 4.0 x4 mode);M.2_2 slot (Key M), type 2242/2260/2280/22110 (supports PCIe 4.0 x4/x2 mode)*;AMD B850 Chipset;M.2_3 slot (Key M), type 2280 (supports PCIe 4.0 x4 mode)**;4 x SATA 6Gb/s ports;* Specifications vary by CPU types.;** The PCIe16(G4) shares bandwidth with M.2_3. The;PCIEX16(G4) will be disabled when M.2_3 runs.;AMD RAIDXpert2 Technology;Ryzen™ 9000 Series Processors: RAID 0/1/5/10;Ryzen™ 8000 Series Processors: RAID 0/1;Ryzen™ 7000 Series Processors: RAID 0/1/10

I/O: 1 x USB 20Gbps port (1 x USB Type-C®);3 x USB 10Gbps ports (3 x Type-A);4 x USB 5Gbps ports (4 x Type-A);2 x USB 2.0 ports (2 x Type-A);1 x DisplayPort;1 x HDMI™ port;1 x Wi-Fi module;1 x Realtek 2.5Gb Ethernet port;5 x Audio jacks;1 x BIOS FlashBack™ button

Connectors: Fan and Cooling Related;1 x 4-pin CPU Fan header;1 x 4-pin CPU OPT Fan header;1 x 4-pin AIO Pump header;4 x 4-pin Chassis Fan headers;Power Related;1 x 24-pin Main Power connector;2 x 8-pin +12V CPU Power connectors;Storage Related;3 x M.2 slots (Key M);4 x SATA 6Gb/s ports;USB;1 x USB 10Gbps connector (supports USB Type-C®);1 x USB 5Gbps header supports 2 additional USB 5Gbps ports;2 x USB 2.0 headers support 4 additional USB 2.0 ports;Miscellaneous;3 x Addressable Gen 2 headers;1 x Clear CMOS header;1 x Chassis Intrusion header;1 x COM Port header;1 x Front Panel Audio header (F_AUDIO);1 x 10-1 pin Front System Panel header;1 x Thunderbolt™ (USB4®) header

Audio: Realtek ALC1220P 7.1 Surround Sound High Definition Audio CODEC;- Impedance sense for front and rear headphone outputs;- Internal audio Amplifier to enhance the highest quality sound for headphone and speakers;- Supports: Jack-detection, Multi-streaming, Front Panel Jack-retasking;- High quality 120 dB SNR stereo playback output and 113 dB SNR recording input (Line-in);- Supports up to 32-Bit/192 kHz playback*;Audio Features;- Audio Shielding;- Premium audio capacitors;- Dedicated audio PCB layers;- Audio cover;- Unique de-pop circuit

LAN: 1 x Realtek 2.5Gb Ethernet;TUF LANGuard

BIOS: 256 Mb Flash ROM, UEFI AMI BIOS

Form Factor: ATX Form Factor, 30.5 cm x 24.4 cm

OS: Windows 11

Цена : 292.37 EUR с ДДС



Наличност: Този продукт е бил добавен в нашия каталог на Пт 10 април, 2026