

МРЕЖОВА ТЕХНИКА > СУИЧОВЕ

D-Link 48 Ports GE PoE (30W) + 4 Ports 10G SFP+ Smart Managed Switch, 370W



Модел : DGS-1530-52P

D-Link 48 Ports GE PoE (30W) + 4 Ports 10G SFP+ Smart Managed Switch, 370W

Суич, тип: Fixed Port

Общ брой портове: 52

Основни портове, тип: 48x10/100/1000Base-T

Power Over Ethernet (PoE): Ports 1 to 48 compliant with both IEEE 802.3af/802.3at, Maximum PoE Budget: 370 W (740 W with DPS-700 RPS redundant power supply)

Uplink портове: 4x10GE SFP

Свободни (10GB) слотове: No

Управление: Web-based GUI, Command Line Interface (CLI), Telnet server/client, Command logging, SNMP v1/v2c/v3 (supports IPv4), SNMP Traps, System log, SMTP (supports IPv4), RMON v1/v2, 802.1AB LLDP, Flash file system, Multiple image, D-Link Discovery Protocol (DDP)

Stackable: Physical Stacking: Up to 80 Gbps stacking bandwidth, Up to 9 switches in a stack, Ring/chain topology support; D-Link Single IP Management (SIM): Up to 32 units per virtual stack

Fans: 3 x Smart fan

Захранване: AC Input: 100 to 240 VAC 50/60 Hz, Max Power Consumption: 482 W (PoE on), 59.2 W (PoE off);

Redundant Power Supply

Routing: Layer 3 Lite

Памет (Flash, RAM): -

Капацитет за маршрутизиране/превключване, Gbps: 176 Gbps

Пропускателна способност, Mpps: 130.95 Mpps

MAC адреси: 16000 MAC address table size

VLAN (брой, стандарти): VLAN group (Max. 4094 VLAN), Port-based/MAC-based VLAN, GVRP (Max. 255 dynamic VLANs), 802.1v Protocol VLAN, Double VLAN (Port-based/Selective Q-in-Q), 802.1Q tagged VLAN, ISM VLAN, VLAN translation, VLAN trunking, Voice VLAN, Private VLAN

QoS: 802.1p; 8 queues per port; Queue Handling: Strict Priority (SP), Weighted Round Robin (WRR), Strict + WRR, Deficit Round Robin (DDR), Weighted Deficit Round Robin (WDRR); Bandwidth control: Port/Flow-based (ingress/egress, min. granularity 64 Kbps)

L2 мрежови стандарти: IEEE 802.3, IEEE 802.3u, IEEE

802.3ab, IEEE 802.3ae, IEEE 802.3x, IEEE 802.1D, IEEE 802.1w, IEEE 802.1s, IEEE 802.1AX, IEEE 802.3ad, IEEE 802.1v, IEEE 802.1Q, IEEE 802.1p, IEEE 802.1X, IEEE 802.3ah, IEEE 802.1ag, IEEE 802.1AB, IEEE 802.3af, IEEE 802.3at

L3 мрежови стандарти: Static route: 64 IPv4 static routes, 32 IPv6 static routes

IPv6 functionality: IPv6 Route Advertisement (RA) Guard, IPv6 ND snooping, IPv6 ND inspection, IPv6 traffic class, IPv6 Flow Label, IPv6 Neighbor Discovery (ND)

Сигурност: SSH v2, TLS 1.2, Port Security (Up to 6656 MAC addresses per port), Broadcast/multicast/unicast storm control, Traffic segmentation, D-Link Safeguard Engine, DHCP server screening, ARP spoofing prevention, BPDU/DoS attack prevention

Размери (Ш, Д, В), mm: 440 x 308 x 44 mm

Опция за монтаж: Desktop or 19" Rack Mount (mounting brackets included)

Цена : 2103.83 EUR с ДДС

Наличност: Този продукт е бил добавен в нашия каталог на Вт 07 юли, 2026