МРЕЖОВА ТЕХНИКА > СУИЧОВЕ

D-Link 8 Ports GE + 2 Ports 10G SFP+ Smart Managed Switch



Модел : DGS-1530-10
D-Link 8 Ports GE + 2 Ports 10G SFP+ Smart Managed Switch
Суич, тип: Fixed Port
Общ брой портове: 10
Основни портове, тип: 8x10/100/1000Base-T
Power Over Ethernet (PoE): No
Uplink портове: 2x10GE SFP
Свободни (10GB) слотове: No
Управление: Web-based GUI, Command Line Interface (CLI), Telnet server/client, Command logging, SNMP v1/v2c/v3 (supports IPv4), SNMP Traps, System log, SMTP (supports IPv4), RMON v1/v2, 802.1AB LLDP, Flash file system, Multiple image, D-Link Discovery Protocol (DDP)
Stackable: Physical Stacking: Up to 80 Gbps stacking bandwidth, Up to 9 switches in a stack, Ring/chain topology support; D-Link Single IP Management (SIM): Up to 32 units per virtual stack
Fans: Fanless
Захранване: AC Input: 100 to 240 VAC 50/60 Hz, Max Power Consumption: 14.6 W, Redundant Power Supply
Routing: Layer 3 Lite
Памет (Flash, RAM): -
Капацитет за маршрутизиране/превключване, Gbps: 56 Gbps
Пропускателна способност, Mpps: 41.67 Mpps
MAC адреси: 16000 MAC address table size
VLAN (брой, стандарти): VLAN group (Max. 4094 VLAN), Port-based/MAC-based VLAN, GVRP (Max. 255 dynamic VLANs), 802.1v Protocol VLAN, Double VLAN (Port-based/Selective Q-in-Q), 802.1Q tagged VLAN, ISM VLAN, VLAN translation, VLAN trunking, Voice VLAN, Private VLAN
QoS: 802.1p; 8 queues per port; Queue Handling: Strict Priority (SP), Weighted Round Robin (WRR), Strict + WRR, Deficit Round Robin (DDR), Weighted Deficit Round Robin (WDRR); Bandwidth control: Port/Flow-based (ingress/egress, min. granularity 64 Kbps)
L2 мрежови стандарти: IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3ae, IEEE 802.3x, IEEE 802.1D, IEEE 802.1w, IEEE 802.1s, IEEE 802.1AX, IEEE 802.3ad, IEEE 802.1v, IEEE 802.1Q, IEEE 802.1p, IEEE 802.1X, IEEE 802.3ah, IEEE 802.1ag, IEEE 802.1AB
L3 мрежови стандарти: Static route: 64 IPv4 static routes,

November 22, 2024, 2:34:2

32 IPv6 static routes
IPv6 functionality: IPv6 Route Advertisement (RA) Guard, IPv6 ND snooping, IPv6 ND inspection, IPv6 traffic class, IPv6 Flow Label, IPv6 Neighbor Discovery (ND)
Сигурност: SSH v2, TLS 1.2, Port Security (Up to 6656 MAC addresses per port), Broadcast/multicast/unicast storm control, Traffic segmentation, D-Link Safeguard Engine, DHCP server screening, ARP spoofing prevention, BPDU/DoS attack prevention
Размери (Ш, Д, В), mm: 280 x 180 x 44 mm
Опция за монтаж: Desktop or 19" Rack Mount (mounting brackets included)

Цена : 529.93 EUR с ДДС

Наличност: Този продукт е бил добавен в нашия каталог на Вт 25 август, 2026

November 21, 2026, 2:31 p.