ОХРАНИТЕЛНА ТЕХНИКА > IP Видео Камери

HikVision 2 MP Acusense Smart Hybrid Light Fixed Dome Network Camera, 2.8 mm, F1.6, IR, White Light up to 30m, H.265+, IP67, built-in arrayed dual-microphone, built-in memory card slot (up to 512GB), 12Vdc/PoE 8.5W



Модел : DS-2CD2123G2-LIS2U
HikVision 2 MP Acusense Smart Hybrid Light Fixed Dome Network Camera, 2.8 mm, F1.6, IR, White Light up to 30m, H.265+, IP67, built-in arrayed dual-microphone, built-in memory card slot (up to 512GB), 12Vdc/PoE 8.5W
Тип: IP
Сензор, тип: CMOS
Размер на оптичния сензор: 1/2.7" Progressive Scan CMOS
Резолюция, MP: 2 MP
Фокално разстояние: 2.8 mm, horizontal FOV 112°, vertical FOV 61°, diagonal FOV 132°
Минимална осветеност, lx: Color: 0.005 Lux @ (F1.6, AGC ON), B/W: 0 Lux with light
IR осветление: IR, White Light up to 30m
Максимална резолюция, pixels: 1920x1080
Формати на компресиране: Main stream: H.265+/H.265/H.264+/H.264; Sub-stream: H.265/H.264 /MJPEG
Скорост на предаване на кадри: Main Stream - 50 Hz: 25 fps (1920x1080, 1280x720), 60 Hz: 30 fps (1920x1080, 1280x720); Sub-Stream - 50 Hz: 25 fps (640x480, 640x360), 60 Hz: 30 fps (640x480, 640x360)
Поддържани мрежови протоколи: TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, UPnP, SMTP, IGMP, 802.1X, QoS, IPv4, IPv6, UDP, Bonjour, SSL/TLS, PPPoE, SNMP, WebSocket, WebSockets
Мрежов интерфейс: 1 RJ45 10 M/100 M self-adaptive Ethernet port
Безжична мрежа: -
Power Over Ethernet (PoE): PoE: IEEE 802.3af, Class 3, max. 8.5 W
Входни/Изходни портове: Alarm: 1 input, 1 output (max. 12 VDC, 30 mA); Audio: 1 input (line in), 1 output (line out)
Звук: Built-in arrayed dual-microphone
Захранване: 12 VDC ± 25%, 0.6 A, max. 7.2 W
Слот за карти: Built-in memory card slot, support microSD/microSDHC/microSDXC card, up to 512 GB
Нощно виждане: IR cut filter

Външен монтаж: yes
Влагозащита: IP67
Вандалоустойчивост: IK10
Работна температура: -30 °C to 60 °C
Диапазон на влажността при експлоатация: Humidity 95% or less (non-condensing)
Сигурност: Password protection, complicated password, HTTPS encryption, IP address filter, Security Audit Log, basic and digest authentication for HTTP/HTTPS, TLS 1.1/1.2/1.3, WSSE and digest authentication for Open Network Video Interface
Размери (Ш, Д, В), mm: 121.5 x 97.6 mm

Цена : 196.80 EUR с ДДС

Наличност: Този продукт е бил добавен в нашия каталог на Ср 08 април, 2026

November 21, 2026, 2:06 a