ОХРАНИТЕЛНА ТЕХНИКА > IP Видео Камери

HikVision 8 MP Acusense Smart Hybrid Light Fixed Bullet Network Camera, 4 mm, F1.6, IR, White Light up to 80m, H.265+, IP67, IK10, built-in Microphone, built-in memory card slot (up to 512GB), 12Vdc/PoE 12W



Модел : DS-2CD2T83G2-4LI
HikVision 8 MP Acusense Smart Hybrid Light Fixed Bullet Network Camera, 4 mm, F1.6, IR, White Light up to 80m, H.265+, IP67, IK10, built-in Microphone, built-in memory card slot (up to 512GB), 12Vdc/PoE 12W
Тип: IP
Сензор, тип: CMOS
Размер на оптичния сензор: 1/2.8" Progressive Scan CMOS
Резолюция, MP: 8 MP
Фокално разстояние: 4 mm, horizontal FOV 88°, vertical FOV 44°, diagonal FOV 105°
Минимална осветеност, lx: Color: 0.005 Lux @ (F1.6, AGC ON), 0 Lux with light
IR осветление: IR, White Light up to 80m
Максимална резолюция, pixels: 3840x2160
Формати на компресиране: Main stream: H.265/H.264/H.264+/H.265+; Sub-stream: H.265/H.264/MJPEG; Third stream: H.265/H.264
Скорост на предаване на кадри: Main Stream - 50Hz: 20fps (3840x2160) 25fps (3200x1800, 2688x1520, 1920x1080, 1280x720), 60Hz: 20fps (3840x2160) 30fps (3200x1800, 2688x1520, 1920x1080, 1280x720); Sub-Stream - 50Hz: 25fps (1280x720,640x480,640x360), 60Hz: 30fps (1280x720,640x480,640x360)
Поддържани мрежови протоколи: TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, UPnP, SMTP, IGMP, 802.1X, QoS, IPv4, IPv6, UDP, Bonjour, SSL/TLS, PPPoE, SNMP, WebSocket, WebSockets
Мрежов интерфейс: 1 RJ45 10 M/100 M self-adaptive Ethernet port
Безжична мрежа: -
Power Over Ethernet (PoE): PoE: IEEE 802.3af, Class 3, max.12 W
Входни/Изходни портове: -
Звук: Built-in Microphone
Захранване: 12 VDC ± 25%, 0.87 A, max. 10.5 W
Слот за карти: Built-in memory card slot, support microSD/microSDHC/microSDXC card, up to 512 GB
Нощно виждане: IR cut filter

Външен монтаж: yes
Влагозащита: IP67
Вандалоустойчивост: IK10
Работна температура: -30 °C to 60 °C
Диапазон на влажността при експлоатация: Humidity 95% or less (non-condensing)
Сигурност: Password protection, complicated password, HTTPS encryption, IP address filter, Security Audit Log, basic and digest authentication for HTTP/HTTPS, TLS 1.1/1.2/1.3, WSSE and digest authentication for Open Network Video Interface
Размери (Ш, Д, В), mm: 88.7 x 93.1 x 286.7 mm

Цена : 339.60 EUR с ДДС

Наличност: Този продукт е бил добавен в нашия каталог на Ср 08 април, 2026

November 21, 2026, 2:06 a