ОХРАНИТЕЛНА ТЕХНИКА > IP Видео Камери

HikVision 4 MP Dual Light MD 2.0 Varifocal Bullet Network Camera, 2.8 to 12 mm, F1.6, IR, White Light up to 50m, H.265+, IP67, built-in microphone, built-in memory card slot (up to 512 GB), 12Vdc/PoE 12.9W



Модел : DS-2CD1643G2-LIZU
HikVision 4 MP Dual Light MD 2.0 Varifocal Bullet Network Camera, 2.8 to 12 mm, F1.6, IR, White Light up to 50m, H.265+, IP67, built-in microphone, built-in memory card slot (up to 512 GB), 12Vdc/PoE 12.9W
Тип: IP
Сензор, тип: CMOS
Размер на оптичния сензор: 1/3" Progressive Scan CMOS
Резолюция, MP: 4 MP
Фокално разстояние: 2.8 to 12 mm, horizontal FOV 96.7° to 29.7°, vertical FOV 51.7° to 16.7°, diagonal FOV 114.3° to 34°
Минимална осветеност, lx: Color: 0.005 Lux @ (F1.6, AGC ON), B/W: 0 Lux with IR
IR осветление: IR, White Light up to 50m
Максимална резолюция, pixels: 2560x1440
Формати на компресиране: Main stream: H.265/H.264/H.264+/H.265+; Sub-stream: H.265/H.264/MJPEG
Скорост на предаване на кадри: Main Stream - 50 Hz: 20 fps (2560x1440) 25 fps (1920x1080, 1280x720), 60 Hz: 20 fps (2560x1440) 24 fps (1920x1080, 1280x720); Sub-Stream - 50 Hz: 25 fps (1280x720, 640x480, 640x360), 60 Hz: 24 fps (1280x720, 640x480, 640x360)
Поддържани мрежови протоколи: TCP/IP, ICMP, DHCP, DNS, HTTP, RTP, RTSP, RTCP, NTP, IGMP, IPv6, UDP, QoS, FTP, SMTP
Мрежов интерфейс: 1 RJ45 10M/100M self-adaptive Ethernet port
Безжична мрежа: -
Power Over Ethernet (PoE): PoE: IEEE 802.3af, Class 3, max. 12 W
Входни/Изходни портове: -
Звук: Built-in microphone
Захранване: 12 VDC ± 25%, 0.88 A, max. 10.5 W
Слот за карти: Built-in memory card slot, support microSD/microSDHC/microSDXC card, up to 512 GB
Нощно виждане: IR cut filter
Външен монтаж: yes

November 2024

Влагозащита: IP67
Вандалоустойчивост: -
Работна температура: -30 °C to 60 °C
Диапазон на влажността при експлоатация: Humidity 95% or less (non-condensing)
Сигурност: Password protection, complicated password, watermark, basic and digest authentication for HTTP, WSSE and digest authentication for Open Network Video Interface, security audit log, host authentication (MAC address)
Размери (Ш, Д, В), mm: 105 x 252 mm

Цена : 217.20 EUR с ДДС

Наличност: Този продукт е бил добавен в нашия каталог на Ср 08 април, 2026

November 21, 2026 2:06 a