ОХРАНИТЕЛНА ТЕХНИКА > IP Видео Камери

HikVision 4 MP Acusense Smart Hybrid Light Fixed Bullet Network Camera, 4 mm, F1.6, IR, White Light up to 40m, H.265+, IP67, built-in arrayed dual-microphone, built-in memory card slot (up to 512GB), 12Vdc/PoE 7.5W



Модел : DS-2CD2043G2-LI2U
HikVision 4 MP Acusense Smart Hybrid Light Fixed Bullet Network Camera, 4 mm, F1.6, IR, White Light up to 40m, H.265+, IP67, built-in arrayed dual-microphone, built-in memory card slot (up to 512GB), 12Vdc/PoE 7.5W
Тип: IP
Сензор, тип: CMOS
Размер на оптичния сензор: 1/2.9" Progressive Scan CMOS
Резолюция, MP: 4 MP
Фокално разстояние: 4 mm, horizontal FOV 84°, vertical FOV 45°, diagonal FOV 100°
Минимална осветеност, lx: Color: 0.005 Lux @ (F1.6, AGC ON), B/W: 0 Lux with light
IR осветление: IR, White Light up to 40m
Максимална резолюция, pixels: 2688x1520
Формати на компресиране: Main stream: H.265/H.264/H.264+/H.265+; Sub-stream: H.265/H.264/MJPEG
Скорост на предаване на кадри: Main Stream - 50 Hz: 25 fps (2688x1520, 1920x1080, 1280x720) 60 Hz: 30 fps (2688x1520, 1920x1080, 1280x720); Sub-Stream - 50 Hz: 25 fps (1280x720, 640x480, 640x360) 60 Hz: 30 fps (1280x720, 640x480, 640x360)
Поддържани мрежови протоколи: TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, UPnP, SMTP, IGMP, 802.1X, QoS, IPv4, IPv6, UDP, Bonjour, SSL/TLS, PPPoE, SNMP, WebSocket, WebSockets
Мрежов интерфейс: 1 RJ45 10M/100M self-adaptive Ethernet port
Безжична мрежа: -
Power Over Ethernet (PoE): PoE: IEEE 802.3af, Class 3, max. 7.5 W
Входни/Изходни портове: -
Звук: Built-in arrayed dual-microphone
Захранване: 12 VDC ± 25%, 0.5 A, max. 6 W
Слот за карти: Built-in memory card slot, support microSD/microSDHC/microSDXC card, up to 512 GB
Нощно виждане: IR cut filter

November 2020

Външен монтаж: yes
Влагозащита: IP67
Вандалоустойчивост: -
Работна температура: -30 °C to 60 °C
Диапазон на влажността при експлоатация: Humidity 95% or less (non-condensing)
Сигурност: Password protection, complicated password, HTTPS encryption, IP address filter, Security Audit Log, basic and digest authentication for HTTP/HTTPS, TLS 1.1/1.2/1.3, WSSE and digest authentication for Open Network Video Interface
Размери (Ш, Д, В), mm: 74.4 x 176.3 mm

Цена : 236.40 EUR с ДДС

Наличност: Този продукт е бил добавен в нашия каталог на Ср 08 април, 2026

November 21, 2026, 2:06 a