ОХРАНИТЕЛНА ТЕХНИКА > IP Видео Камери

HikVision 4 MP AcuSense Strobe Light and Audible Warning Fixed Turret Network Camera, 2.8 mm, F1.4, IR up to 30m, H.265+, IP67, built-in microphone, built-in Speaker, built-in memory card slot (up to 512 GB), 12Vdc/PoE 8.8W



Модел : DS-2CD2346G2-ISU/SL(C)
HikVision 4 MP AcuSense Strobe Light and Audible Warning Fixed Turret Network Camera, 2.8 mm, F1.4, IR up to 30m, H.265+, IP67, built-in microphone, built-in Speaker, built-in memory card slot (up to 512 GB), 12Vdc/PoE 8.8W
Тип: IP
Сензор, тип: CMOS
Размер на оптичния сензор: 1/3" Progressive Scan CMOS
Резолюция, MP: 4 MP
Фокално разстояние: 2.8 mm, horizontal FOV 103°, vertical FOV 55°, diagonal FOV 123°
Минимална осветеност, lx: Color: 0.003 Lux @ (F1.4, AGC ON), B/W: 0 Lux with IR
IR осветление: IR up to 30m
Максимална резолюция, pixels: 2688x1520
Формати на компресиране: Main stream: H.265/H.264/H.264+/H.265+; Sub-stream: H.265/H.264/MJPEG
Скорост на предаване на кадри: Main Stream - 50 Hz: 25 fps (2688x1520, 1920x1080, 1280x720) 60 Hz: 30 fps (2688x1520, 1920x1080, 1280x720); Sub-Stream - 50 Hz: 25 fps (1280x720, 640x480, 640x360) 60 Hz: 30 fps (1280x720, 640x480, 640x360)
Поддържани мрежови протоколи: TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, NTP, UPnP, SMTP, IGMP, 802.1X, QoS, IPv4, IPv6, UDP, Bonjour, SSL/TLS, PPPoE, SNMP, ARP, WebSocket, WebSockets
Мрежов интерфейс: 1 RJ45 10M/100M self-adaptive Ethernet port
Безжична мрежа: -
Power Over Ethernet (PoE): PoE (802.3af, 36 V to 57 V), 0.25 A to 0.15 A, max. 8.8 W
Входни/Изходни портове: Alarm: 1 input, 1 output (max. 24 VDC/24 VAC, 500 mA); Audio: 1 input (line in), 1 output (line out)
Звук: Built-in speaker and microphone
Захранване: 12 VDC, 0.65 A, max. 7.8 W
Слот за карти: Built-in micro SD/SDHC/SDXC slot, up to

512 GB
Нощно виждане: IR cut filter
Външен монтаж: yes
Влагозащита: IP67
Вандалоустойчивост: -
Работна температура: -30 °C to 60 °C
Диапазон на влажността при експлоатация: Humidity 95% or less (non-condensing)
Сигурност: Password protection, complicated password, HTTPS encryption, IP address filter, Security Audit Log, basic and digest authentication for HTTP/HTTPS, TLS 1.1/1.2, WSSE and digest authentication for Open Network Video Interface
Размери (Ш, Д, В), mm: 138.3 x 124.5 mm

Цена : 253.20 EUR с ДДС

Наличност: Този продукт е бил добавен в нашия каталог на Ср 08 април, 2026

November 21, 2026 2:06 a