ОХРАНИТЕЛНА ТЕХНИКА > IP Видео Камери

HikVision 4 MP Acusense Smart Hybrid Light Motorized Varifocal Bullet Network Camera, 2.8 to 12 mm, F1.6, IR,White Light up to 60m, 120 dB WDR, H.265+, IP67, IK10, built-in arrayed dual-microphone, built-in memory card slot (up to 512 GB), 12Vdc/PoE 15W



Модел : DS-2CD2643G2-LIZS2U
HikVision 4 MP Acusense Smart Hybrid Light Motorized Varifocal Bullet Network Camera, 2.8 to 12 mm, F1.6, IR,White Light up to 60m, 120 dB WDR, H.265+, IP67, IK10, built-in arrayed dual-microphone, built-in memory card slot (up to 512 GB), 12Vdc/PoE 15W
Тип: IP
Сензор, тип: CMOS
Размер на оптичния сензор: 1/3" Progressive Scan CMOS
Резолюция, MP: 4 MP
Фокално разстояние: 2.8 to 12 mm: horizontal FOV 102.4° to 31.2°, vertical FOV 54.7° to 17.6°, diagonal FOV 122.1° to 35.8°
Минимална осветеност, lx: Color: 0.005 Lux @ (F1.6, AGC ON), B/W: 0 Lux with light
IR осветление: IR, White Light up to 60m
Максимална резолюция, pixels: 2688x1520
Формати на компресиране: Main stream: H.265/H.264/H.264+/H.265+; Sub-stream: H.265/H.264/MJPEG
Скорост на предаване на кадри: Main Stream - 50 Hz: 25 fps (2688x1520, 1920x1080, 1280x720) 60 Hz: 30 fps (2688x1520, 1920x1080, 1280x720); Sub-Stream - 50 Hz: 25 fps (1280x720, 640x480, 640x360) 60 Hz: 30 fps (1280x720, 640x480, 640x360)
Поддържани мрежови протоколи: TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, UPnP, SMTP, IGMP, 802.1X, QoS, IPv4, IPv6, UDP, Bonjour, SSL/TLS, PPPoE, SNMP, WebSocket, WebSockets
Мрежов интерфейс: 1 RJ45 10M/100M self-adaptive Ethernet port
Безжична мрежа: -
Power Over Ethernet (PoE): PoE: IEEE 802.3at, Class 4, max. 15 W
Входни/Изходни портове: Alarm: 1 input, 1 output (max. 24 VDC/24 VAC, 1 A); Audio: 1 input (line in), 1 output (line out)
Звук: Built-in arrayed dual-microphone

Захранване: 12 VDC ± 25%, 1.08 A, max. 13 W
Слот за карти: Built-in memory card slot, support microSD/microSDHC/microSDXC card, up to 512 GB
Нощно виждане: IR cut filter
Външен монтаж: yes
Влагозащита: IP67
Вандалоустойчивост: IK10
Работна температура: -30 °C to 60 °C
Диапазон на влажността при експлоатация: Humidity 95% or less (non-condensing)
Сигурност: Password protection, complicated password, HTTPS encryption, IP address filter, Security Audit Log, basic and digest authentication for HTTP/HTTPS, TLS 1.1/1.2/1.3, WSSE and digest authentication for Open Network Video Interface
Размери (Ш, Д, В), mm: 332.8 x 97.9 x 94.2 mm

Цена : 426.00 EUR с ДДС

Наличност: Този продукт е бил добавен в нашия каталог на Ср 08 април, 2026

November 21, 2025, 2:06 a