

ОХРАНИТЕЛНА ТЕХНИКА > IP Видео Камери

## HikVision 4 MP Smart Hybrid Light with ColorVu Fixed Turret Network Camera, 2.8 mm, F1, IR, White Light up to 30m, H.265+, IP67, 130 dB WDR, built-in microphone, built-in speaker, built-in memory card slot (up to 512 GB), 12Vdc/PoE 10.5W



Модел : DS-2CD2347G2H-LISU/SL

HikVision 4 MP Smart Hybrid Light with ColorVu Fixed Turret Network Camera, 2.8 mm, F1, IR, White Light up to 30m, H.265+, IP67, 130 dB WDR, built-in microphone, built-in speaker, built-in memory card slot (up to 512 GB), 12Vdc/PoE 10.5W

Тип: IP

Сензор, тип: CMOS

Размер на оптичния сензор: 1/1.8" Progressive Scan CMOS

Резолюция, MP: 4 MP

Фокално разстояние: 2.8 mm, horizontal FOV 111.1°, vertical FOV 57.6°, diagonal FOV 138.5°

Минимална осветеност, lx: Color: 0.0005 Lux @ (F1.0, AGC ON), 0 Lux with light

IR осветление: IR, White Light up to 30m

Максимална резолюция, pixels: 2688x1520

Формати на компресиране: Main stream:

H.265/H.264/H.264+/H.265+; Sub-stream:

H.265/H.264/MJPEG

Скорост на предаване на кадри: Main Stream - 50 Hz: 25 fps (2688x1520, 1920x1080, 1280x720) 60 Hz: 30 fps (2688x1520, 1920x1080, 1280x720); Sub-Stream - 50 Hz: 25 fps (1280x720, 640x480, 640x360) 60 Hz: 30 fps (1280x720, 640x480, 640x360)

Поддържани мрежови протоколи: TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, UPnP, SMTP, IGMP, 802.1X, QoS, IPv4, IPv6, UDP, Bonjour, SSL/TLS, PPPoE, SNMP, WebSocket, WebSockets, SRTP, SFTP

Мрежов интерфейс: 1 RJ45 10M/100M self-adaptive Ethernet port

Безжична мрежа: -

Power Over Ethernet (PoE): PoE: IEEE 802.3af, Class 3, max. 10.5 W

Входни/Изходни портове: Alarm: 1 input, 1 output (max. 24 VDC/24 VAC, 1 A); Audio: 1 input (line in), 1 output (line out)

Звук: Built-in microphone and speaker

Захранване: 12 VDC  $\pm$  25%, 0.75 A, max. 9 W

Слот за карти: Built-in memory card slot, support microSD/microSDHC/microSDXC card, up to 512 GB

Нощно виждане: IR cut filter

Външен монтаж: yes

Влагозащита: IP67

Вандалоустойчивост: -

Работна температура: -30 °C to 60 °C

Диапазон на влажността при експлоатация: Humidity 95% or less (non-condensing)

Сигурност: Password protection, complicated password, HTTPS encryption, 802.1X authentication (EAP-TLS, EAP-LEAP, EAP-MD5), watermark, IP address filter, basic and digest authentication for HTTP/HTTPS, WSSE and digest authentication for Open Network Video Interface

Размери (Ш, Д, В), mm: 138.3 x 115.4 mm

Цена : 294.00&nbsp;EUR с ДДС

*Наличност: Този продукт е бил добавен в нашия каталог на Ср 08 април, 2026*