

ОХРАНИТЕЛНА ТЕХНИКА > IP Видео Камери

## HikVision 4 MP Panoramic AcuSense Fixed Bullet Network Camera, 2.8 mm, F1.6, IR up to 40m, H.265+, IP67, 120 dB WDR, built-in microphone, built-in speaker, built-in memory card slot (up to 512 GB), 12Vdc/PoE 12.5W



Модел : DS-2CD2T46G2P-ISU/SL(C)

HikVision 4 MP Panoramic AcuSense Fixed Bullet Network Camera, 2.8 mm, F1.6, IR up to 40m, H.265+, IP67, 120 dB WDR, built-in microphone, built-in speaker, built-in memory card slot (up to 512 GB), 12Vdc/PoE 12.5W

Тип: IP

Сензор, тип: CMOS

Размер на оптичния сензор: 2x 1/2.5" Progressive Scan CMOS

Резолюция, MP: 4 MP

Фокално разстояние: 2.8 mm, horizontal FOV: 180°, vertical FOV: 81°

Минимална осветеност, lx: Color: 0.003 Lux @ (F1.6, AGC ON), B/W: 0 Lux with IR

IR осветление: IR up to 40m

Максимална резолюция, pixels: 3040x1368

Формати на компресиране: Main stream:

H.265/H.264/H.264+/H.265+; Sub-stream:

H.265/H.264/MJPEG

Скорост на предаване на кадри: Main Stream - 50 Hz: 25 fps (3040x1368), 60 Hz: 24 fps (3040x1368); Sub-Stream - 50 Hz: 25 fps (1200x536, 960x432), 60 Hz: 24 fps (1200x536, 960x432)

Поддържани мрежови протоколи: TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, UPnP, SMTP, IGMP, 802.1X, QoS, IPv4, IPv6, UDP, Bonjour, SSL/TLS, PPPoE, SNMP, Websocket, Websockets

Мрежов интерфейс: 1 RJ45 10M/100M self-adaptive Ethernet port

Безжична мрежа: -

Power Over Ethernet (PoE): PoE: IEEE 802.3af, Class 3, 36 V to 57 V, 0.35 A to 0.22 A, max. 12.5 W

Входни/Изходни портове: Alarm: 1 input, 1 output (max. 24 VDC/24 VAC, 1 A); Audio: 1 input (line in), 1 output (line out)

Звук: Built-in microphone and speaker

Захранване: 12 VDC  $\pm$  25%, 0.88 A, max. 10.5 W

Слот за карти: Built-in memory card slot, support microSD/microSDHC/microSDXC card, up to 512 GB

Нощно виждане: IR cut filter  
Външен монтаж: yes  
Влагозащита: IP67  
Вандалоустойчивост: -  
Работна температура: -30 °C to 60 °C  
Диапазон на влажността при експлоатация: Humidity  
95% or less (non-condensing)  
Сигурност: Password protection, complicated password,  
HTTPS encryption, 802.1X authentication (EAP-MD5),  
watermark, IP address filter, basic and digest authentication  
for HTTP/HTTPS, WSSE and digest authentication for Open  
Network Video Interface, RTP/RTSP over HTTPS  
Размери (Ш, Д, В), mm: 118.6 x 105.1 x 306.5 mm

Цена : 288.00&nbsp;EUR с ДДС

*Наличност: Този продукт е бил добавен в нашия каталог на Ср 08 април, 2026*