ОХРАНИТЕЛНА ТЕХНИКА > IP Видео Камери

HikVision 4 MP Panoramic AcuSense Fixed Bullet Network Camera, 2.8 mm, F1.6, IR up to 40m, H.265+, IP67, 120 dB WDR, built-in microphone, built-in speaker, built-in memory card slot (up to 512 GB), 12Vdc/PoE 12.5W



Модел : DS-2CD2T46G2P-ISU/SL(C)
HikVision 4 MP Panoramic AcuSense Fixed Bullet Network Camera, 2.8 mm, F1.6, IR up to 40m, H.265+, IP67, 120 dB WDR, built-in microphone, built-in speaker, built-in memory card slot (up to 512 GB), 12Vdc/PoE 12.5W
Тип: IP
Сензор, тип: CMOS
Размер на оптичния сензор: 2x 1/2.5" Progressive Scan CMOS
Резолюция, MP: 4 MP
Фокално разстояние: 2.8 mm, horizontal FOV: 180°, vertical FOV: 81°
Минимална осветеност, lx: Color: 0.003 Lux @ (F1.6, AGC ON), B/W: 0 Lux with IR
IR осветление: IR up to 40m
Максимална резолюция, pixels: 3040x1368
Формати на компресиране: Main stream: H.265/H.264/H.264+/H.265+; Sub-stream: H.265/H.264/MJPEG
Скорост на предаване на кадри: Main Stream - 50 Hz: 25 fps (3040x1368), 60 Hz: 24 fps (3040x1368); Sub-Stream - 50 Hz: 25 fps (1200x536, 960x432), 60 Hz: 24 fps (1200x536, 960x432)
Поддържани мрежови протоколи: TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, UPnP, SMTP, IGMP, 802.1X, QoS, IPv4, IPv6, UDP, Bonjour, SSL/TLS, PPPoE, SNMP, Websocket, Websockets
Мрежов интерфейс: 1 RJ45 10M/100M self-adaptive Ethernet port
Безжична мрежа: -
Power Over Ethernet (PoE): PoE: IEEE 802.3af, Class 3, 36 V to 57 V, 0.35 A to 0.22 A, max. 12.5 W
Входни/Изходни портове: Alarm: 1 input, 1 output (max. 24 VDC/24 VAC, 1 A); Audio: 1 input (line in), 1 output (line out)
Звук: Built-in microphone and speaker
Захранване: 12 VDC ± 25%, 0.88 A, max. 10.5 W
Слот за карти: Built-in memory card slot, support microSD/microSDHC/microSDXC card, up to 512 GB

November 2024

Нощно виждане: IR cut filter
Външен монтаж: yes
Влагозащита: IP67
Вандалоустойчивост: -
Работна температура: -30 °C to 60 °C
Диапазон на влажността при експлоатация: Humidity 95% or less (non-condensing)
Сигурност: Password protection, complicated password, HTTPS encryption, 802.1X authentication (EAP-MD5), watermark, IP address filter, basic and digest authentication for HTTP/HTTPS, WSSE and digest authentication for Open Network Video Interface,RTP/RTSP over HTTPS
Размери (Ш, Д, В), mm: 118.6 x 105.1 x 306.5 mm

Цена : 333.60 EUR с ДДС

Наличност: Този продукт е бил добавен в нашия каталог на Ср 08 април, 2026

November 21, 2026 2:06 a