

ОХРАНИТЕЛНА ТЕХНИКА > IP Видео Камери

## HikVision 4 MP Outdoor Audio Fixed Bullet Network Camera, 4 mm, F1.6, IR up to 30m, H.265+, IP66, 80 dB WDR, 2 Antennas, built-in microphone, built-in speaker, built-in memory card slot (up to 512 GB), 12Vdc/6W



Модел : DS-2CV2041G2-IDW(4MM)(W)

HikVision 4 MP Outdoor Audio Fixed Bullet Network Camera, 4 mm, F1.6, IR up to 30m, H.265+, IP66, 80 dB WDR, 2 Antennas, built-in microphone, built-in speaker, built-in memory card slot (up to 512 GB), 12Vdc/6W

Тип: IP

Сензор, тип: CMOS

Размер на оптичния сензор: 1/3" Progressive Scan CMOS

Резолюция, MP: 4 MP

Фокално разстояние: 4 mm, horizontal FOV 79°, vertical FOV 40°, diagonal FOV 94°

Минимална осветеност, lx: Color: 0.005 Lux @ (F1.6, AGC ON), B/W: 0 Lux with IR

IR осветление: IR up to 30m

Максимална резолюция, pixels: 2560x1440

Формати на компресиране: Main stream:

H.265+/H.265/H.264+/H.264, Sub-stream:

H.265/H.264/MJPEG

Скорост на предаване на кадри: Main Stream - 50 Hz: 20 fps (2560x1440), 25 fps (1920x1080, 1280x720), 60 Hz: 20 fps (2560x1440), 30 fps (1920x1080, 1280x720);

Sub-Stream - 50 Hz: 25 fps (1280x720, 640x480, 640x360), 60 Hz: 30 fps (1280x720, 640x480, 640x360)

Поддържани мрежови протоколи: TCP/IP, ICMP, HTTP, HTTPS, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, QoS, IPv6, Bonjour

Мрежов интерфейс: 1 RJ45 10M/100M self-adaptive Ethernet port

Безжична мрежа: 802.11n: OFDM, 802.11b: DSSS, 802.11g: OFDM

Power Over Ethernet (PoE): -

Входни/Изходни портове: -

Звук: Built-in microphone and speaker

Захранване: 12 VDC  $\pm$  25%, 0.5 A, max. 6 W

Слот за карти: Built-in memory card slot, support microSD/microSDHC/microSDXC card, up to 512 GB

Нощно виждане: IR cut filter

Външен монтаж: yes

Влагозащита: Water and dust resistant (IP66)



Вандалоустойчивост: -  
Работна температура: -30 °C to 60 °C  
Диапазон на влажността при експлоатация: Humidity  
95% or less (non-condensing)  
Сигурност: Password protection, complicated password,  
HTTPS encryption, IP address filter, Security Audit Log, basic  
and digest authentication for HTTP/HTTPS  
Размери (Ш, Д, В), mm: 175.6 x 73 x 89.1 mm

Цена : 84.00&nbsp;EUR с ДДС

*Наличност: Този продукт е бил добавен в нашия каталог на Ср 08 април, 2026*