

ОХРАНИТЕЛНА ТЕХНИКА > IP Видео Камери

HikVision 4 MP 4x Zoom IR Wi-Fi Mini PT Dome Network Camera, 2.8 to 12 mm, F1.5, IR up to 50m, white light distance: up to 6 m, H.265+, IP66, 120 dB WDR, built-in microphone, built-in speaker, built-in memory card slot (up to 256 GB), 12Vdc/PoE/16W



Модел : DS-2DE3A404IWG-E/W

HikVision 4 MP 4x Zoom IR Wi-Fi Mini PT Dome Network Camera, 2.8 to 12 mm, F1.5, IR up to 50m, white light distance: up to 6 m, H.265+, IP66, 120 dB WDR, built-in microphone, built-in speaker, built-in memory card slot (up to 256 GB), 12Vdc/PoE/16W

Тип: IP

Сензор, тип: CMOS

Размер на оптичния сензор: 1/2.8" Progressive Scan CMOS

Резолюция, MP: 4 MP

Фокално разстояние: 2.8 to 12 mm, horizontal field of view: 96.7° to 31.6° (wide-tele), vertical field of view: 51.1° to 17.7° (wide-tele), diagonal field of view: 115.1° to 36.3° (wide-tele)

Минимална осветеност, lx: Color: 0.005 Lux @(F1.5, AGC ON); B/W: 0.001 Lux @(F1.5, AGC ON); 0 Lux with IR

IR осветление: IR up to 50m, white light distance: up to 6 m

Максимална резолюция, pixels: 2560x1440

Формати на компресиране: Main stream:

H.265+/H.265/H.264+/H.264, Sub-stream:

H.265/H.264/MJPEG, Third stream: H.265/H.264/MJPEG

Скорост на предаване на кадри: Main Stream - 50 Hz: 25 fps (2560x1440, 1920x1080, 1280x960, 1280x720), 60 Hz: 30 fps (2560x1440, 1920x1080, 1280x960, 1280x720); Sub-Stream - 50 Hz: 25 fps (704x576, 640x480, 352x288), 60 Hz: 30 fps (704x480, 640x480, 352x240); Third Stream

Поддържани мрежови протоколи: IPv4/IPv6, HTTP, HTTPS, QoS, FTP, SMTP, UPnP, SNMP, DNS, DDNS, NTP, RTSP, RTP, TCP/IP, DHCP, PPPoE, Bonjour

Мрежов интерфейс: 1 RJ45 10M/100M self-adaptive Ethernet port

Безжична мрежа: IEEE802.11b, 802.11g, 802.11n

Power Over Ethernet (PoE): PoE (802.3at), 42.5 to 57 VDC, 0.6 A Max. 16 W (including max. 2.4 W for IR, 1.2 W for white light flashing)

Входни/Изходни портове: Audio: 1 input (line in), 1 output (line out), Alarm: 1 input, 1 output

Звук: Built-in microphone and speaker
Захранване: 12 VDC, 3.33 A
Слот за карти: Built-in memory card slot, support microSD/microSDHC/microSDXC card, up to 256 GB
Нощно виждане: IR cut filter
Външен монтаж: yes
Влагозащита: Water and dust resistant (IP66)
Вандалоустойчивост: -
Работна температура: -30 °C to 65 °C
Диапазон на влажността при експлоатация: Humidity 90% or less (non-condensing)
Сигурност: Password protection, complicated password, HTTPS encryption, watermark, IP address filter, basic and digest authentication for HTTP/HTTPS, RTP/RTSP over HTTPS, control timeout settings, security audit log, TLS 1.2, host authentication (MAC address)
Размери (Ш, Д, В), mm: 179.3 x 120.5 x 182 mm
Допълнителни функции: Zoom: 4x optical, 16x digital

Цена : 385.20 EUR с ДДС

Наличност: Този продукт е бил добавен в нашия каталог на Ср 08 април, 2026