

ОХРАНИТЕЛНА ТЕХНИКА > IP Видео Камери

HikVision 4-inch 4 MP 25X Powered by DarkFighter IR Network Speed Dome, 4.8 mm to 120 mm, F1.6, IR up to 100m, H.265+, IP66, 120 dB WDR, built-in memory card slot (up to 256 GB), 12Vdc/PoE+/24W



Модел : DS-2DE4425IW-DE(T5)

HikVision 4-inch 4 MP 25X Powered by DarkFighter IR Network Speed Dome, 4.8 mm to 120 mm, F1.6, IR up to 100m, H.265+, IP66, 120 dB WDR, built-in memory card slot (up to 256 GB), 12Vdc/PoE+/24W

Тип: IP

Сензор, тип: CMOS

Размер на оптичния сензор: 1/2.8" Progressive Scan CMOS

Резолюция, MP: 4 MP

Фокално разстояние: 4.8 mm to 120 mm, horizontal field of view: 55° to 2.4° (wide-tele), vertical field of view: 33° to 1.4° (wide-tele), diagonal field of view: 61.5° to 2.8° (wide-tele)

Минимална осветеност, lx: Color: 0.005 Lux @ (F1.6, AGC ON); B/W: 0.001 Lux @ (F1.6, AGC ON), 0 Lux with IR

IR осветление: IR up to 100m

Максимална резолюция, pixels: 2560x1440

Формати на компресиране: Main stream:

H.265+/H.265/H.264+/H.264, Sub-stream:

H.265/H.264/MJPEG, Third stream: H.265/H.264/MJPEG

Скорост на предаване на кадри: Main Stream - 50 Hz: 25 fps (2560x1440, 1920x1080, 1280x960, 1280x720), 60 Hz: 30 fps (2560x1440, 1920x1080, 1280x960, 1280x720); Sub-Stream - 50 Hz: 25 fps (704x576, 640x480, 352x288), 60 Hz: 30 fps (704x480, 640x480, 352x240); Third Stream

Поддържани мрежови протоколи: IPv4/IPv6, HTTP, HTTPS, 802.1x, QoS, FTP, SMTP, UPnP, SNMP, DNS, DDNS, NTP, RTSP, RTCP, RTP, TCP/IP, UDP, IGMP, ICMP, DHCP, PPPoE, Bonjour, Websocket, Websockets

Мрежов интерфейс: 1 RJ45 10M/100M self-adaptive Ethernet port

Безжична мрежа: -

Power Over Ethernet (PoE): PoE (802.3at)

Входни/Изходни портове: Audio: 1 input (line in), 1 output (line out), Alarm: 1 input, 1 output

Звук: -

Захранване: 12 VDC, max. 18 W, including max. 1.6 W for heater and 9 W for IR

Слот за карти: Built-in memory card slot, support

microSD/SDHC/SDXC card, up to 256 GB

Нощно виждане: IR cut filter

Външен монтаж: yes

Влагозащита: Water and dust resistant (IP66)

Вандалоустойчивост: -

Работна температура: -30 °C to 65 °C

Диапазон на влажността при експлоатация: Humidity 90% or less (non-condensing)

Сигурност: Password protection, complicated password, HTTPS encryption, 802.1X authentication (EAP-TLS, EAP-LEAP, EAP-MD5), watermark, IP address filter, basic and digest authentication for HTTP/HTTPS, RTP/RTSP over HTTPS, control timeout settings

Размери (Ш, Д, В), mm: 164.5 x 290 mm

Допълнителни функции: Zoom: 25x optical, 16x digital

Цена : 576.00 EUR с ДДС

Наличност: Този продукт е бил добавен в нашия каталог на Ср 08 април, 2026