

ОХРАНИТЕЛНА ТЕХНИКА > IP Видео Камери

HikVision 7-inch 4 MP 32X Powered by DarkFighter IR Network Speed Dome, 5.9 mm to 188.8 mm, F1.5, IR up to 200m, H.265+, IP66, IK10, 120 dB WDR, built-in speaker, built-in memory card slot (up to 256 GB), 24Vac/Hi-PoE/42W



Модел : DS-2DE7A432IW-AEB(T5)

HikVision 7-inch 4 MP 32X Powered by DarkFighter IR Network Speed Dome, 5.9 mm to 188.8 mm, F1.5, IR up to 200m, H.265+, IP66, IK10, 120 dB WDR, built-in speaker, built-in memory card slot (up to 256 GB), 24Vac/Hi-PoE/42W

Тип: IP

Сензор, тип: CMOS

Размер на оптичния сензор: 1/1.8" progressive scan CMOS

Резолюция, MP: 4 MP

Фокално разстояние: 5.9 mm to 188.8 mm, horizontal field of view: 50.8° to 2.6° (wide-tele), vertical field of view: 29.4° to 1.5° (wide-tele), diagonal field of view: 57.4° to 3° (wide-tele)

Минимална осветеност, lx: Color: 0.005 Lux @ (F1.5, AGC ON), B/W: 0.001 Lux@(F1.5, AGC ON), 0 Lux with IR

IR осветление: IR up to 200m

Максимална резолюция, pixels: 2560x1440

Формати на компресиране: Main stream:

H.265+/H.265/H.264+/H.264, Sub-stream:

H.265/H.264/MJPEG, Third stream: H.265/H.264/MJPEG

Скорост на предаване на кадри: Main Stream - 50 Hz: 25 fps (2560x1440, 1920x1080, 1280x960, 1280x720), 60 Hz: 24 fps (2560x1440, 1920x1080, 1280x960, 1280x720); Sub-Stream - 50 Hz: 25 fps (704x576, 640x480, 352x288), 60 Hz: 24 fps (704x480, 640x480, 352x240); Third Stream

Поддържани мрежови протоколи: IPv4/IPv6, HTTP, HTTPS, 802.1x, QoS, FTP, SMTP, UPnP, SNMP, DNS, DDNS, NTP, RTSP, RTCP, RTP, TCP/IP, UDP, IGMP, ICMP, DHCP, PPPoE, Bonjour, Websocket, Websockets

Мрежов интерфейс: 1 RJ45 10M/100M self-adaptive Ethernet port

Безжична мрежа: -

Power Over Ethernet (PoE): Hi-PoE

Входни/Изходни портове: Audio: 1 input (line in), 1 output (line out), Alarm: 2 input, 1 output

Звук: Built-in speaker

Захранване: 24 VAC, max. 42 W (including max. 18 W for IR and max. 10 W for heater)

Слот за карти: Built-in memory card slot, support microSD/SDHC/SDXC card, up to 256 GB

Нощно виждане: IR cut filter

Външен монтаж: yes

Влагозащита: Water and dust resistant (IP66)

Вандалоустойчивост: IK10

Работна температура: -30 °C to 65 °C

Диапазон на влажността при експлоатация: Humidity 90% or less (non-condensing)

Сигурност: Password protection, complicated password, HTTPS encryption, 802.1X authentication (EAP-TLS, EAP-LEAP, EAP-MD5), watermark, IP address filter, basic and digest authentication for HTTP/HTTPS, RTP/RTSP over HTTPS, control timeout settings

Размери (Ш, Д, В), mm: 220 x 363.3 mm

Допълнителни функции: Zoom: 32x optical, 16x digital

Цена : 918.00 EUR с ДДС

Наличност: Този продукт е бил добавен в нашия каталог на Ср 08 април, 2026