

ОХРАНИТЕЛНА ТЕХНИКА > IP Видео Декодери

HikVision 32-ch 1.5U K Series AcuSense 4K NVR, 32 IP Cameras, 256 Mbps, up to 12 MP (1x12 MP/2x8 MP/4x4 MP/8x1080p), H.265+, 4 SATA HDD up to 10TB, 2 x USB 2.0, 1 x USB 3.0, Video input: HDMI 4K, VGA 1080p, Audio Output: 1-ch, RCA (Linear, 1 kOhm)



Модел : DS-7732NXI-K4

HikVision 32-ch 1.5U K Series AcuSense 4K NVR, 32 IP Cameras, 256 Mbps, up to 12 MP (1x12 MP/2x8 MP/4x4 MP/8x1080p), H.265+, 4 SATA HDD up to 10TB, 2 x USB 2.0, 1 x USB 3.0, Video input: HDMI 4K, VGA 1080p, Audio Output: 1-ch, RCA (Linear, 1 kOhm)

Тип: IP Recorder

Брой канали: 32 (IP Video Input)

HDMI: 1-ch, 4K (3840 x 2160)/30 Hz, 2K (2560 x 1440)/60 Hz, 1920 x 1080/60 Hz, 1600 x 1200/60 Hz, 1280 x 1024/60 Hz, 1280 x 720/60 Hz, 1024 x 768/60 Hz

VGA: 1-ch, 1920 x 1080/60 Hz, 1280 x 1024/60 Hz, 1280 x 720/60 Hz

Видео изходен режим: HDMI/VGA independent output

Капацитет: Incoming: 256 Mbps, Outgoing: 160 Mbps

Аудио: 1-ch, RCA (2.0 Vp-p, 1 kOhm, using the audio input); Audio Output: 1-ch, RCA (Linear, 1 kOhm)

Видео компресия: H.265/H.265+/H.264+/H.264

Аудио компресия: G.711ulaw/G.711alaw/G.722/G.726/AAC

Резолюция на запис: 12 MP/8 MP/6 MP/5 MP/4 MP/3 MP/1080p/UXGA/ 720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF

Дистанционна връзка: 128

Мрежови протоколи: TCP/IP, DHCP, IPv4, IPv6, DNS, DDNS, NTP, RTSP, SADP, SMTP, SNMP, NFS, iSCSI, ISUP, UPnP, HTTP, HTTPS

Мрежов интерфейс: 2 RJ-45 10/100/1000 Mbps self-adaptive Ethernet interface

Спомагателен интерфейс: 4 SATA interfaces (Capacity: Up to 10 TB capacity for each HDD); Front panel: 2x USB 2.0; Rear panel: 1x USB 3.0; Serial Interface: 2 RS-485 (half-duplex), 1 RS-232; Alarm In/Out: 16/4 (16/9 is optional)

Захранване: 100 to 240 VAC, 50 to 60 Hz; Consumption: <= 20 W (without HDD)

Power Over Ethernet (PoE): -

Размери (Ш, Д, В), mm: 445 x 400 x 75 mm

Тегло, g: <= 5 kg

Цена : 631.20 EUR с ДДС



Наличност: Този продукт е бил добавен в нашия каталог на Ср 08 април, 2026

April 11, 2026, 4:28 pm