

ОХРАНИТЕЛНА ТЕХНИКА > IP Видео Декодери

## **HikVision 8-ch 1U AcuSense 4K NVR, 8 IP Cameras, 80 Mbps, up to 12 MP/4K, H.265+, 2 SATA HDD up to 14TB, 1 x USB 2.0, 1 x USB 3.0, Video input: HDMI 4K, VGA 1080p, Audio Output: 1-ch, RCA (Linear, 1 kOhm)**



Модел : DS-7608NXI-I2/S(E)

HikVision 8-ch 1U AcuSense 4K NVR, 8 IP Cameras, 80 Mbps, up to 12 MP/4K, H.265+, 2 SATA HDD up to 14TB, 1 x USB 2.0, 1 x USB 3.0, Video input: HDMI 4K, VGA 1080p, Audio Output: 1-ch, RCA (Linear, 1 kOhm)

Тип: IP Recorder

Брой канали: 8 (IP Video Input)

HDMI: 4K (3840 x 2160)/30 Hz, 2K (2560 x 1440)/60 Hz, 1920 x 1080/60 Hz, 1600 x 1200/60 Hz, 1280 x 1024/60 Hz, 1280 x 720/60 Hz, 1024 x 768/60 Hz

VGA: 1920 x 1080/60 Hz, 1280 x 1024/60 Hz, 1280 x 720/60 Hz, 1024 x 768/60 Hz

Видео изходен режим: HDMI/VGA independent output

Капацитет: Incoming: 80 Mbps, Outgoing: 256 Mbps

Аудио: 1-ch, RCA (2.0 Vp-p, 1 kOhm); Audio Output: 1-ch, RCA (Linear, 1 kOhm)

Видео компресия: H.265/H.265+/H.264+/H.264

Аудио компресия:

G.711ulaw/G.711alaw/G.722/G.726/AAC/MP2L2/PCM

Резолюция на запис: 32 MP/24 MP/12 MP/8 MP/6 MP/5

MP/4 MP/3 MP/1080p/UXGA/720p/VGA

/4CIF/DCIF/2CIF/CIF/QCIF (The NVR supports up to 4-ch 32 MP/24 MP IP video inputs)

Дистанционна връзка: 128

Мрежови протоколи: TCP/IP, DHCP, IPv4, IPv6, DNS, DDNS, NTP, RTSP, SADP, SMTP, SNMP, NFS, iSCSI, ISUP, UPnP, HTTP, HTTPS

Мрежов интерфейс: 2 RJ-45 10/100/1000 Mbps self-adaptive Ethernet interface

Спомагателен интерфейс: 2 SATA interfaces (Capacity: Up to 14 TB capacity for each HDD); Front panel: 1x USB 2.0; Rear panel: 1x USB 3.0; Alarm In/Out: 4/1

Захранване: 100 to 240 VAC, 50 to 60 Hz; Consumption: <math>\leq 30\text{ W}</math> (without HDD)

Power Over Ethernet (PoE): -

Размери (Ш, Д, В), mm: 385 x 317 x 52 mm

Тегло, g: <math>\leq 2.5\text{ kg}</math>

Цена : 514.80&nbsp;EUR с ДДС



Наличност: Този продукт е бил добавен в нашия каталог на Ср 08 април, 2026

June 23, 2026, 4:59 am