

МРЕЖОВА ТЕХНИКА > СУИЧОВЕ

Cisco Catalyst 1200 8-port GE, Ext PS, 2x1G Combo



Модел : C1200-8T-E-2G

Cisco Catalyst 1200 8-port GE, Ext PS, 2x1G Combo

Суич, тип: Fixed Port

Общ брой портове: 10

Основни портове, тип: 8x10/100/1000Base-T

Power Over Ethernet (PoE): -

Uplink портове: 2x SFP/ RJ-45 combo

Свободни (10GB) слотове: -

Управление: Network PnP, Web user interface, Cisco Business mobile app, Cisco Business Dashboard, SNMP, MIBs, RMON, DHCP, CLI and etc.

Stackable: -

Fans: Fanless

Захранване: 100 to 240V 50 to 60 Hz, external

Routing: Layer 3 static routing

Памет (Flash, RAM): 512 MB (Flash), 1 GB DDR4 (DRAM), 1.5 MB (Packet buffer)

Капацитет за маршрутизиране/превключване, Gbps: 20 Gbps

Пропускателна способност, Mpps: 14.88 Mpps

MAC адреси: 8000 addresses

VLAN (брой, стандарти): Support for up to 255 active VLANs simultaneously; Port-based and 802.1Q tag-based VLANs, Management VLAN, Guest VLAN, Auto Surveillance VLAN (ASV), Voice VLAN

QoS: 8 hardware queues; Port based, 802.1p VLAN priority based, IPv4/v6 IP precedence/Type of Service (ToS)/DSCP based, Differentiated Services (DiffServ), classification and re-marking ACLs, trusted QoS

L2 мрежови стандарти: IEEE 802.3, IEEE 802.3u/ab/ad/z/x/af/at; IEEE 802.1D (STP)/1Q/p VLAN/w RSTP/s Multiple STP/X Port Access Authentication; RFC

IPv6 functionality: IPv6 host mode, IPv6 over Ethernet, Dual IPv6/IPv4 stack, IPv6 Neighbor Discovery (ND), IPv6 stateless address auto-configuration, Path MTU discovery, DAD, ICMP v6, IPv6 over IPv4 network with ISATAP

Сигурност: SSL, SSH, IEEE 802.1X (authenticator role): RADIUS authentication, guest VLAN, single/multiple host mode, and single/multiple sessions; STP; SCT; SSD, Trustworthy systems, Port security, Storm control, DoS prevention, ACLs

Размери (Ш, Д, В), mm: 268 x 185 x 44 mm

Опция за монтаж: Desktop



Цена : 226.50 EUR с ДДС

Наличност: Този продукт е бил добавен в нашия каталог на Вт 28 април, 2026

April 30, 2026, 11:55 PM