

МРЕЖОВА ТЕХНИКА > СУИЧОВЕ

## Cisco Catalyst 9200L 24-port PoE+ 4x10G uplink Switch, Network Essentials



Модел : C9200L-24P-4X-E

Cisco Catalyst 9200L 24-port PoE+ 4x10G uplink Switch, Network Essentials

Суич, тип: Fixed Port

Общ брой портове: 28

Основни портове, тип: 24x10/100/1000Base-T

Power Over Ethernet (PoE): IEEE 802.3at PoE+ (up to 30W per port), Perpetual PoE, Fast PoE; Available PoE Power:

370W\* (Default primary power supply - PWR-C5-600WAC),

740W\* (Optional secondary power supply -

PWR-C5-600WAC), \*Limited by port number and port rating

Uplink портове: 4x10GBase-T

Свободни (10GB) слотове: No

Управление: SNMPv1, SNMPv2c, and SNMPv3; RMON I and II standards; Internet Group Management Protocol (IGMP); CLI; TCP; UDP

Stackable: Cisco StackWise-80 stacking ports: copper-based Cisco StackWise cabling, Stacking hardware (C9200L-STACK-KIT=), Supported stack members: Other C9200L models with same license level (8 Number of members)

Fans: Fixed redundant

Захранване: Dual field-replaceable power supplies,

Default primary AC power supply: PWR-C5-600WAC

Routing: Layer 3 Advanced

Памет (Flash, RAM): Flash memory: 4 GB; RAM: 2 GB DRAM

Капацитет за маршрутизиране/превключване, Gbps: 128 Gbps

Пропускателна способност, Mpps: 190.4 Mpps

MAC адреси: 16000 MAC address

VLAN (брой, стандарти): VLAN IDs: 1024; IEEE 802.1Q VLAN

QoS: Granular wireless bandwidth management and fair sharing, 802.1p Class of Service (CoS) and Differentiated Services Code Point (DSCP) field classification, Shaped Round Robin (SRR) scheduling, Committed Information Rate (CIR), and eight egress queues per port

L2 мрежови стандарти: IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3z, IEEE 802.3bz, IEEE 802.3ad, IEEE 802.3af, IEEE 802.3at, IEEE 802.1D, IEEE 802.1p, IEEE 802.1Q, IEEE 802.1s, IEEE 802.1w, IEEE 802.1x, IEEE

