

МРЕЖОВА ТЕХНИКА > Access Points

Cisco Catalyst Wireless 9162I AP (W6E, tri-band 2x2) w/Reg E



Модел : CW9162I-E

Cisco Catalyst Wireless 9162I AP (W6E, tri-band 2x2) w/Reg E

Скорост: 802.11ac: PHY data rates up to 866.7 Mbps (2x2 80 MHz on 5 GHz); 802.11n v2: PHY data rates up to 444.4 Mbps (40 MHz with 5 GHz and 20 MHz with 2.4 GHz)

Антенa: Integrated antenna (internal antenna, omnidirectional in azimuth): 2.4 GHz: Peak gain 4 dBi, 5 GHz: Peak gain 5 dBi, 6 GHz: Peak gain 5 dBi

Интерфейс: 1x 100M/1000M/2.5G Multigigabit Ethernet (RJ-45) port; Management console port (RJ-45); USB 2.0 at 4.5W

Стандарти: IEEE 802.3, IEEE 802.3ab, IEEE 802.3af/at/bt, IEEE 802.11a/b/g/n/ac/ax, IEEE 802.11h, 802.11d

Сигурност: WPA2-Personal (802.11i), WPA2-Enterprise with 802.1X, WPA3-Personal, WPA3-Enterprise, WPA3-Enhanced Open (OWE), Advanced Encryption Standard (AES); EAP

Захранване: 802.3bt, Cisco Universal PoE (Cisco UPOE), 802.3at Power over Ethernet Plus (PoE+), 802.3af PoE; Max PoE Power Consumption: 25.5W (PoE+); DC power input (12V/ MA-PWR-30W)

Управление: Allow you to choose between on-premises and cloud management; Cisco Smart Software Manager (SSM)

Размери, mm: 200 x 200 x 44.45 mm (without mounting brackets)

Тегло, g: 930 g

Други: System memory: 2048 MB DRAM, 1024 MB flash

Цена : 756.31 EUR с ДДС

Наличност: Този продукт е бил добавен в нашия каталог на Вт 28 април, 2026